

IP Gateway with RS232/RS485 Port

Model: IP-COM-PORT



TIS

THIS

Data Sheet Rev 3.1

KEY BENEFITS

- Programming and communication port
- TIS Cloud server connection
- Modbus protocol master/slave controller
- 3rd party communication such as cool master and UPB Lights...

KEY FEATURES

- 🖈 Standard 35 mm Din-Rail mounted
- 🖈 Rs232 / Rs485 Port
- 🖈 Works with TIS-BUS protocol

TIS

Hexadecimal / ASCII code Communication





IP COMMUNICATION PORT IP Gateway with RS232/RS485 Port

Model: IP-COM-PORT







PRODUCT SPECIFICATIONS			
Ŷ	Ports	RS232 RS485 RJ45	RS232 ASCII / HEX 2 way connection Modbus, RS485 ASCII / HEX 2 way connection Ethernet UDP - TCP/IP connection
$\langle \cdot \rangle$	Reaction time		approx. 20ms
¢°	Function programmable options	RS232 RS485 Ethernet Rj45 Upgrading PRG button	Sending 1980 × 15 ASCII characters messages, Receiving 99 × 15 ASCII characters messages Modbus RTU Slave/Master option Sending 1980 × 15 ASCII characters messages Receiving 99 × 15 ASCII characters messages UDP TIS Protocol – TCP/IP TIS Claude By UDP Ethernet port To reset IP address to 192.168.10.100 (default)
ţ0	Mounting	Din Rail Wall mount	Standard 35 mm Din rail screw holder on the back of the module
<u>199</u>	Connection terminal	Load and Power Data / bus	Screw terminal 0,254mm2 Male/female connectors Link + screw Terminal
Ö	Weight	Without packaging	0.21 KG
ŀ <u>+</u> •	Dimensions	Width x length x height	90mm x 73mm x 76mm
	Housing	Materials Casing color IP rating	ABS anti fire Black Gray IP 20
	Temperature range	Operation Storage Transport	-3060°C -2060°C -3075°C

Air humidity

0



<85% non-condensing



TIS Logo is a Registered Trademark of Texas Intelligent System LLC in the United States of America. This company takes TIS Control Ltd. in other countries. All of the Specifications are subject to change without notice.

SUITE# 610. 860 NORTH DOROTHY DR RICHARDSON TX 75081.USA

RM 1502-p9 Easey CommBldg 253-261 Hennessy Rd Wanchai Hong Kong