



Sutherland Acrylic PVA

PRODUCT DESCRIPTION

Sutherland Acrylic PVA is an affordable acrylic PVA developed for use on interior and exterior surfaces.

PRODUCT FEATURES

- Smooth Matt Finish
- High hiding
- High Build - covers minor flaws
- Lead free
- For use on exterior and interior walls.
- Used on suitably prepared new plaster, concrete, porous brickwork and various types of building boards.

TECHNICAL INFORMATION

Colour:	White and 7 colours
Appearance:	Matt finish
S.G.:	±1.35
Viscosity:	±120 KU
Spreading rate:	6m ² /litre depending on surface porosity
Solvent:	Water
Packaging:	25 litres

SURFACE PREPARATION

All surfaces are to be clean, dry & free of oil, grease, dirt & old flaking paint. Should the substrates be powdery or weak, it is recommended to remove as much as possible of the loose powdery surface. Then seal with at least 1 coat of Sutherland Prime&Seal . Allow to dry for 2 hours at 25°C prior to painting with Sutherland Acrylic PVA.

APPLICATION

Apply two or three coats to new surfaces so as to achieve complete obliteration.
Suitable for application by brush or roller.

ENVIRONMENT

It is recommended that application be confined to the following:

Surface temperature:	Min. 15°C	Max. 40°C
Ambient temperature:	Min. 15°C	Max. 40°C
Relative humidity:	Min.0%	Max.85%

Or at least 3°C above Dew point

Do not leave container open, as skin forms on the surface of the paint.

DRYING TIME

Touch dry 30 min at 23 °C
Dry to handle 1 h at 23 °C

OVERCOATING TIMES

Recoating 1 h at 23 °C

LIMITATIONS

NOT recommended for use in paint systems along with other sheen emulsion paints on exterior surfaces.

Avoid painting during inclement weather or if temperature is below 5 °C.

At no time should painting be done in inclement weather or before 9am & after 2pm in winter.

SAFETY PRECAUTIONS

No known problems resulting from contact with skin, however, remove as soon as possible with soap and water. Avoid ingestion and contact with eyes. If ingested, seek medical attention. Do not induce vomiting. If paint contact is made with eyes, rinse eyes well with water & seek medical attention. Do not smoke when painting.
Ensure good ventilation during painting and drying.

KEEP OUT OF REACH OF CHILDREN.

Information Provided is based on Laboratory evaluations and data believed to be reliable.
Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for their own use.
It is not to be considered a guarantee of the products properties.

For more information contact our Factories:
Western Cape: Tel/Fax: (021) 853-8105 Mpumalanga: Tel: (013) 246-2570 Fax: (013) 246-2573