



# LOW COAT

## PRODUCT DESCRIPTION

An Acrylic emulsion paint based paint. Formulated to provide good performance at an economical price.

## PRODUCT FEATURES

- . Ease of application
- . Good hiding power.
- . Ease of over coating.
- . Available in standard colours.
- . Ideal for marking of trees and under ground blasting identification.

## TECHNICAL INFORMATION

Colour: Black, White, Green, Dark green, Brown, Blue and Yellow  
Appearance: Matt finish  
Generic type: Acrylic co-polymer.  
Total solids: 50%  
S.G.: 1.02  
Viscosity: 112 Ku  
Spreading rate: 3 m<sup>2</sup> per litre.  
Solvent: Water  
Artificial weathering: Good  
Opacity: Translucent

## SURFACE PREPARATION

All surfaces are to be clean dry and contamination free.  
I.

## APPLICATION

Stir contents thoroughly, use as supplied. Do not dilute. 3 Coats of 50µ each are recommended for optimum results. Allow a minimum of 4 hours between coats at 25°C

Airless spray: Not suitable  
Conventional spray: Not suitable  
Brush and Roller: Suitable as supplied. Do not dilute.  
Clean up: Wash with Water

## ENVIRONMENT

It is recommended that application be confined to the following:

Surface temperature: 40 degrees C  
Ambient temperature: 40 degrees c  
Relative humidity: 80 %

## DRYING TIME

Substrate Temp	Touch Dry	Hard Dry
15°C	3 hours	8 hours
20°C	1.5 hours	6 hours
25°C	45 minutes	4 hours
30°C	30 minutes	2 hours

## OVERCOATING TIMES

15°C: 8 hours  
20°C: 6 hours  
25°C: 4 hours  
30°C: 3 hours

## LIMITATIONS

Sustained cold conditions can result in paint failure.  
Avoid painting on wet substrates and in wet conditions

## STORAGE AND HANDLING

Store in a cool and dry area, away from heat, direct sunlight and severe cold.

## SAFETY PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN.

Information Provided is based on Laboratory evaluations and data believed to be reliable.  
Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for their own use.  
It is not to be considered a guarantee of the products properties.

For more information contact our Factories:  
Western Cape: Tel/Fax: (021) 853-8105 Mpumalanga: Tel: (013) 246-2570 Fax: (013) 246-2573