



◆ SPECIFICATION

Model NO.	IPRGMTE605XHL200	IPRGMTE605XHP200
Camera		
Image Sensor	IMX307	IMX327
Main processor	Hi3516C	Hi3516C
Resolution	2MP 1080P	2MP 1080P
Effective Pixels	1945(H)*1097(V)	1945(H)*1097(V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG	
TV System	PAL/NTSC	
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec	
S/N Ratio	≥52dB	
Scanning System	Progressive	
Video Output	Network	
Reset Button	Optional	
Lens		
Focus Length	2.7-13.5mm	2.7-13.5mm
Focus Control	Auto	Auto
Lens Type	Motorized	Motorized
Pixels	3M	3M
Night Vision		
Infrared LED	42μ x 4PCS	
Infrared Distance	40M	
IR Status	Auto Control	
IR Power On	Auto Control	
Network		
Ethernet	RJ-45 (10/100Base-T)	
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP	
ONVIF	Support ONVIF 2.4	
P2P	YES, Support QR Code	
POE	Optional, Support IEEE 802.3af	
Video Delay	0.3S (Within the Lan)	
Main Stream 1	2048*1536@15fps	2048*1536@15fps
Main Stream 2	1920*1080@30fps	1920*1080@30fps
Main Stream 3	1280*720@30fps	1280*720@30fps
Sub Stream 1	720*480@15fps 720*480@30fps	720*480@15fps 720*480@30fps
Sub Stream 2	/	/
Sub Stream 3	/	/
Tri Stream	352*288@15fps 352*288@30fps	352*288@15fps 352*288@30fps
IE Brower	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53), Mac Safari	
Smart Phone	iPhone, iPad, Android, Android Pad	
Camera Features		
Day/Night	Color/ B&W (IR-CUT)	
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control), Video Tampering	
Full Starlight	/	/
Corridor Pattern	Support	Support
Defog Mode	Support	Support
ROI	Support	Support
BLC	Support	Support
HDR	/	/
WDR	Support	Support
Motion Detection	Support	Support
Privacy Masking	3 Rectangular Zone	3 Rectangular Zone
Recording Mode	NVR/NAS/CMS/Web	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands	
Interface		
Audio	Optional	Optional
Alarm	/	/
SD Card Slot	Optional, Support Max 128GB	Optional, Support Max 128GB
RS485	/	/
General		
Housing	IP66	
Anti-cut Bracket	NO	
IR Cut Filter	YES	
Operation Temperature	-20℃ ~ +60℃ RH95% Max	
Storage Temperature	-20℃ ~ +60℃ RH95% Max	
Power Source	DC12V±10%,1000mA	
Dimension	179(W) x 90(H) x 90(D)mm	
Weight	1.6kgs(Without bracket)	

RGM Digital

No. 100, Section 1, Taiwan Boulevard, Central District, Taichung City, Taiwan

Tel. No.: 886-4-2561-2199 Homepage: <http://www.rgm-digital.com> Email: sales@rgm-digital.com