



GLASSGO PAINTS

## SUPER SHEEN WHITE DATA SHEET

DATE ISSUED: 2018-01-31

### **SECTION 1. MANUFACTURER**

Glassgo Paints

### **SECTION 2. DESCRIPTION**

Product Name: Super sheen pva

### **SECTION 3. PRODUCT BENEFITS**

A Tough, durable and washable sheen finish for interior and exterior use

### **SECTION 4. PREPERATION**

Ensure that all surfaces are clean, free from dust, oil, grease or other contaminants before painting

### **SECTION 5. TECHNICAL DATA**

Type	: Pure Acrylic Polymer
Gloss Level	: Semi - Gloss
Re Coating Time	: 5 - 6 Hours
Viscosity	: 100 - 115 ku's
Practical Spread Rate	: 4 - 6 m <sup>2</sup>
Specific Gravity	: 1 - 1.25 dep on colour
Solid by volume	: 48 %
Solid by Mass	: 42 - 46 %
Drying Time	: Surface 30 min
Recommended DFT	: 30 - 35 micron per coat. 2 Coats recommended

### **SECTION 6. COLOUR RANGE**

Wide range of colors from colorworks tinting system

### **SECTION 7. METHODS OF APPLICATION**

Brush, roller and airless spray

### **SECTION 8. THINNING**

Not Recommended

### **SECTION 9. CLEAN UP**

Water

### **SECTION 10. PACKAGING**

1L, 5L, 20L, 200L

### **SECTION 11. FLASHPOINT**

Non - flammable.

