

BLIND RIVETS

TUV
CERT
ISO9001:2008


AS 5056 Aluminium Alloy Rivets with Steel Mandrels

IP-114/Grade10


RIVET CODE	RIVET DIAMETER D	HOLE SIZE (inch)	RIVET LENGTH L(max.)	GRIP RANGE G	HEAD DIAMETER H	HEAD THICKNESS T(max.)	STANDARD STRENGTH Lbs (min.)	
							SHEAR	TENSILE
32 34 36	3/32 } 0.0938	0.097 } 0.100	0.250 0.375 0.500	1/32-1/8 1/8-1/4 1/4-3/8	0.178 } 0.198	0.032	90 400N	120 530N
41 42 43 44 45 46 48 410 412	1/8 } 0.1250	0.129 } 0.133	0.212 0.275 0.337 0.400 0.462 0.525 0.650 0.775 0.901	1/32-1/16 1/16-1/8 1/8-3/16 3/16-1/4 1/4-5/16 5/16-3/8 3/8-1/2 1/2-5/8 5/8-3/4	0.238 } 0.262	0.040	170 760N	220 980N
52 53 54 55 56 58 510 512	5/32 } 0.1562	0.160 } 0.164	0.300 0.362 0.425 0.487 0.550 0.675 0.800 0.925	1/32-1/8 1/8-3/16 3/16-1/4 1/4-5/16 5/16-3/8 3/8-1/2 1/2-5/8 5/8-3/4	0.296 } 0.328	0.050	260 1160N	350 1560N
62 63 64 65 66 68 610 612 614 616	3/16 } 0.1875	0.192 } 0.196	0.325 0.387 0.450 0.513 0.575 0.700 0.825 0.950 1.075 1.200	1/32-1/8 1/8-3/16 3/16-1/4 1/4-5/16 5/16-3/8 3/8-1/2 1/2-5/8 5/8-3/4 3/4-7/8 7/8-1	0.356 } 0.394	0.060	380 1690N	500 2230N
84 86 88 810 812 814	1/4 } 0.250	0.257 } 0.261	0.500 0.625 0.750 0.875 1.000 1.125	1/32-1/4 1/4-3/8 3/8-1/2 1/2-5/8 5/8-3/4 3/4-7/8	0.475 } 0.525	0.080	700 3120N	920 4100N

1"=25.4mm (1 inch=25.4 millimeter)

- These rivets are installed quickly and easily from one side of the workpiece.
- Rivets with countersunk heads and colored heads are manufactured to order.



Domed Head



Countersunk Head 120°

SRC-111003

Due to continuous development we reserve the right to alter specifications without prior notice.