


I'm not robot  reCAPTCHA

Continue

Um unico ponto de compras para todos os produtos de suas Marcas prediletas 1 2 3 4 5 6 7 8 8 9 10 11 12 13 14 15 16 17 18 18 19 20 21 22 23 25 25 26 27 28 28 290 31 32 Page 2 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 18 19 20 21 21 22 23 24 25 26 27 28 29 30 31 31 32 Disc 32

DISC HILL PIR 1 1 1. INTRODUCTION DISC is the smallest 360° installed by a passive infrared detector currently on the market. Disc provides an almost conical pattern with a maximum diameter of 10.5 m (36 feet) when installed on a ceiling of 3.6 m (12 feet). False alarms caused by environmental disturbances are virtually eliminated through an alternative polar pulse oncoming signal g and a low-noise pyroelectric detector. 2. SPECIFICATIONS OPTICAL Detection Pattern: Almost a conical pattern with a diameter of no more than 10.5 m when installed on a ceiling of 3.6 m (12 feet). COVERAGE PATTERNS DISC Pattern is almost conical (from detector to floor). See Figure 1. The maximum height of the installation is 3.6 m. The floor-level coating pattern is according to the following table: Montage Impulse Height Graf 1 2.4 m (8 ft) 7.3 m dims. (24ft. diam.) 3m (10ft.) 9m diam. (30ft. diam.) 3.6m (12ft.) 11m diam. (36ft. diam.) TENSIONS: 9 to 15.5VDC. Current: 15mA at 12 VDC (21 mA max.). Relay output: Usually closed (safe) contacts. 18 ohm resistor in lots with contacts. Rating - 0.1A resistive/24VDC. Anxious period: 2-7 seconds Tamper Contacts: Usually closed. Rating - 0.5A resistive/ 24VDC. LED: Walk Test is on or off with an internal link. Detector: Two-state pyroelectric detector with low noise. Pulse counter: two position selectors, 1 or 2 pulses with alternative polarity signal processing. 3. METRE 3.1 Pir DISC montage is installed on the ceiling. The maximum height of the installation is 3.6 m (12 feet). A. Mount the device so that the expected movement of the attacker is perpendicular to the detector, not the detector. Be sure to install a detector on a stable ceiling to avoid vibrations. Note: Passive infrared detectors are sensitive to changes in infrared energy caused by an object moving through the device's vision area. The detection of changes in infrared energy depends on the amount of infrared energy transmitted by the moving object and the temperature difference between the object and the background. Because of this, PIR may not react under certain temperature and background conditions where the temperature difference is too low. B. DISC is extremely immune to air turbulence and RFI interference. D-1111-0 DISC Installation Instructions Pulse Count 2 6.4 m diam. (21ft. diam.) 7.3 m diam. (24ft. diam.) 9.1m diam. (30ft. diam.) MOUNTING Ceiling Installation: Maximum installation height of 3.6 m (12 ft) ENVIRONMENTAL Operating temperature: -10°C to 49°C (14°F to 120°F). Temperature 20°C to 60°C (-4°F to 140°F). РАЗМЕРЫ PHYSICAL PHYSICAL x H) : 86 x 24 mm (3-3/8 x 15/16 in). Weight: 64 grams (2 ounces) Color: White. Figure 1 - DISC PIR Coverage pattern However, to minimize possible false alarms, it is recommended to avoid aiming the detector at heaters, light sources, or windows exposed to direct sunlight. Avoid mounting DISC in places where aerial drafts can flow from the ceiling or from cramped walls. Also avoid wiring next to high-speed electrical cables. C. Hold the base of the unit, as shown in Figure 2. Turn the lid counterclockwise until it stops. Separate the lid from the base. Note: If the lid does not separate easily from the base, insert a 1/8 screwdriver between the tab (on the cover) and the slot (on the base). Lower the screwdriver handle until the base is separated from the lid and easily removed. COVER High Figure 2 - Removing the cover of BASE 1 Hi, I have a K9-85 MCW sensor and would like to remove it from the system as I no longer require one in the living room. I trawled the internet for a way to do this, but found nothing to entrust the removal of the unit (from the system, not from the wall, I did it !!!!) anyone who can help, as all guides show installation and inclusion rather than disabling. Thanks to Go to the installation menu, enroll and then choose the zone, then he will talk off remove, click diarm

normal_5f8707600e4f2.pdf
normal_5f870f9d439fc.pdf
normal_5f870917efa9a.pdf
normal_5f8712fbd21c1.pdf
normal_5f8703bdd32dc.pdf
apk film indirme programı
panasonic lumix dmc fz1000 user guide
ben hill griffin
montreal phone chat line
duel links deck building guide
spelling words with meaning and pronunciation pdf
ncert biology class 11 pdf in bengali
install whatsapp apk mirror
descargar groove music para android
mpow 059 bluetooth headphones user guide
simple present tense usage pdf
normal_5f8705f2efd53.pdf
normal_5f870b9f052dc.pdf
normal_5f86f6b348568.pdf
normal_5f8718a46cb2b.pdf