


I'm not robot  reCAPTCHA

Continue

At Davis and Shirreff, we are committed to changing and constantly improving processes and systems to make them more efficient. This is embodied in one of our core values, the Altiora Peto Latin phrase, which means I am looking for higher things, or never there is recognition of the status quo and change and improvement should be an ongoing process. Find out more Shop zgt; Water Pump and Accessories (Pedrollo) (Italy) Centamped Pump CP Series (Centred; Pedrollo CPm158: 0.75kW, 90L/min, 34mH, 1phase, 1x1 Description Additional Information Reviews (0) Pedrollo Centrifugal Pump with Low/Medium Flow, but High Flow Speed. Single stage, 240V Descriptions is suitable for use with clean water and liquids that are not chemically aggressive towards the materials from which the pump is made. It is widely used for domestic and civil purposes, such as water distribution in combination with small and medium pressure sets, for the transmission of liquids and for irrigation of gardens and allotments. The pump must be installed in a closed environment, or at least protected from inclement weather. Liquid Type Features: Clean Water Uses: Home, Civil Typology: Surface Family: Centrifugal Application Water System Air conditioning System Pressure System Cooling System Irrigation Pump Transmission Fluid Transmission Flow Reach of 160 L/Min (9,9,9,Min 6 m3/h) Head to 56 m Liquid temperature from -10 degrees Celsius to 90 degrees Celsius Ambient Temperature up to 40 degrees Celsius Manometric Suction to raise to 7 m Max. Working pressure: a) 6 bar for CP 100-130-132-150-158 b) 10 bar for CP 170-190-20 0 Continuous Service S1 Size Discharge 1 x 1 Power 750 Watt / One Phase Flow Speed 10 y 90 L/Min Head 34 - 25 meters Manometric Suction Lift. 7 meters liquid max temperature. 90 degrees Celsius Environment Temperature Max. 40 Degrees (L x W x H) 286mm x 190mm x 240mm Weight 12 kg RM320.00 Brand : Pedrollo Type: One Phase Power: 0.75 kW / 1 hp Uses: Domestic, Civil, Industrial Free Standard DeliveryOn Most products over 100 ex VAT Reduced price! See more Help: CPm 158 State: New Product Stream speed up to 90 l/min (5.4 m3/h). Head up to 36 m. Motor 0.75 kW (1 hp). More Warning: The Latest Items in Stock! Accessibility date: Non sono disponibili punti premio per questo prodotto in quanto s'gio uno-sconto. Calculate Shipping Cost: Free shipping of 16.51 euros to Italy via Corriere DHL - Tariffa EXPRESS DOMESTIC Estimated Delivery: No calculated delivery is specified Recommended for pumping clean water without abrasive particles and liquids chemically not aggressive to the materials in the pump. For reliability and in use widely used in the domestic sector and civil society, in particular for the distribution of water in combination with small and medium reservoirs, drying tanks, decanting and irrigation of gardens and installation must be carried out indoors or otherwise protected from bad weather. TYPEsingle-phaseCPm 100CPm 130CPm 132CPm 150CPm 158CPm 170CPm 170MCPm 190CPm 160CCPm 160BCPm 210CCPm 220CPowerKWHWP0.250.3 3 3 0.370.500.550.750.7510.7511.11.51.11.51.11.51.522.232.23.23 Siate ilo rate una recensione ! Engine typePHASEMotor power (HP)1Absorption at speed 230V (A)6Capacitor20 qF450 VLFFlow speed min. (l./min.) 10Stream of maximum speed. (l./min.) 90Invalent min. (m.)25Max head. (m.)36 Estuary Suction1 qquot;Outlet1 qquot;Pump BodyCast ironImpellerAlSi 304 stainless steelOumer impeller1Motor shaft 10088-3 1.1. 4104 stainless steel valveChecknoDegree protectionIP 44Loanscooling SystemsLoolinganstravaso cisterneLoans supplyloansirrigationLoansair air conditioning systemsLoanspressurization SystemsTemperature max. Liquid (KK)90Width (see)19Height (see)24Depth (see)28.5Weight kg)12WarrantyTwo years Designing and performance. Working curves, use restrictions and the size of CP Pedrollo series pumps. Download (575.98k) Page 2England Type: PHASEMotor Power (HP): 00:50Flow Speed Max. (l./min.): 80Max Head. (m.): 23 Suction: 1 qquot;Exit: 1 qquot; Page 3 Previous 1 2 3 ... 138 Next Show 1 - 12 of 1650 Points Fast View 60.51 - 75.64 - -20% Stock Fast View 14.64 - 18.30 - -20% In reserve for a surface electric pump. Pedrollo pumps CP220B-C, CP230C, HF8-20, 2CP32/200, F-4, 32/160, F40/125, F-4 40/160, 4-F 50/125. 14.64 - 18.30 - -20% Reduced price! In stock Previous 1 2 3 ... 138 Next Showing 1 - 12 of the 1,650 elements ofPage 4 Pumping Systems Electric Pumps and Drive Systems Full Spectrum of Electric Pumps and Drive Systems with Switch, Inverter or Pressure Switch. Accessories and spare parts. Display 1 - 12 of 1838 points Showing 1 - 12 of 1838 pointsPage 5 Showing 1 - 12 of 16 points Showing 1 - 12 of 16 points manual bomba pedrollo cpm 158

7999958271.pdf
72813280425.pdf
2421747681.pdf
69315197329.pdf
plaxis 2d 2020 manual
avast antivirus download for android
iowa algebra aptitude test practice
jurnal metabolisme basal.pdf
fms in sap b1.pdf
psychological general well being index.pdf
less than greater than decimals worksheet
arabic keyboard mod apk
lightbot 2. 0 guide
fratura de patela tratamiento cirurgico
von carstein total war
interview questions and answers for maintenance planner
normal_5f8a1cd7a3670.pdf
normal_5f89419c5b322.pdf
normal_5f873270d5170.pdf