




I'm not robot



Continue

Bulldog remote starter manual

Click here to view our new instructional video Deluxe 200 Deluxe 200B Deluxe 62i Deluxe 12i Deluxe 22i Models RS92-92E Models RS102-RS112-RS122 Models RS202 - RS202E Model RS302 Model RS602E Model Deluxe 62 Model Deluxe 12/22 Door Lock Types FASD Wire Chart OEM Wire Chart Models 901-902-903-908 Model 1001 Model 1101 Model 2002Pro Models 2001-2004 Model 2003 Model 2020 Model 3001 Model 5002PRO Model 6002PRO Model 7002PRO Models KE1702 RA10 Remote Anything Model 721 Model 781 Model 718 Model UT-B2 Model 706 Model 727 Model 742 CHR-3, CHR-1, CHR-2, SAT-1 GM-5, GM-2, GM-1 NIS-1, NIS-4, TOY-1, TOY-3, TOY-2 HON-2, HON-1 GM-7, GM-6 FD-2 FD-1 GM-3 Model 1302 Silent Guard OEM Wire Chart FASD Wire Chart Model 2001 Models RS202-202E Model 781 Models RS102/112/122 Model 1702Model 2010 Model RS1100-1100E Model RS1200-1200E CONTENTSREMOTE STARTER MODEL RS82INSTALLATION GUIDE-OWNER'S GUIDETechnical AssistanceAll tech personnel are expertly qualified to answer any technical questions. Οι τεχνικοί είναι διαθέσιμοι από Δευτέρα έως Παρασκευή από τις 9:00 π.μ. έως τις 8:00 μ.μ. και το Σάββατο 10:00 π.μ. μέχρι τις 4:00 μ.μ.Address288 Canton Avenue • Wintersville, Οχάιο 43953Τηλεφωνικό Τηλέφωνο: 740-264-4710 • 800-878-8007 • Fax: 740-264-7306Συστήματα συστήματος

1Συστήματα συστήματος	1Απαιτημένος εργαλεία	1Τεχνική βοήθεια	1Πρώτα αρχίσει
links	1-2Επιτεύξεις	2Δημιουργία συνδέσεων καλωδίωσης	& Create
change	4-5Connecting the 11-pin belt and the 4 relay belt..	6 Security	
system	6Working anti-theft	7How to use your remote transmitter.....	7Programming
instructions.....	7 © 1996-2014, Amazon.com, Inc. or its subsidiaries 1 2 3 4 5 6 7 8 Page		
2CONNECTES OF 11-PIN HARNESS & 4-RELAY ORGS ORGS WHT/BLK 16 ga. WHITE 16 ga. YEL/BLK 16 ga. WHT/BLK 16 ga WHITE 16 ga YEL/BLK 16 ga Tap here when installing bypass module 781 or 791. CAUTION: Before connecting the 11-pin belt to the unit, check all connections again to make sure they are safe and properly wrapped with electrical tape. Connect the 11-pin belt to the main control unit. Connect the 3-pin belt from the 4 relay zone to the unit. NOTE: The GRAY cable in the 11-pin belt will not be used. Cables that are not in use should be glued up, not clipd or removed. Press the start button, if the unit receives a signal and your vehicle does not start and does not work, you may have a factory anti-theft system. MODEL RS82 LAST PROGRAMING INSTRUCTIONS WITH THE Addition of additional remote controls The hood must be open. Then press and hold and hold #1 to the work transmitter for six (6) seconds or until the Ignition relay clicks or the engine lamp flashes once, checking the #1 release button. Press and release any button on the new remote control. The ignition relay will click or the control engine light will flash three (3) times, it will close the hood, the new remote control will work now. Tach/Tachless Option Press and hold the brake. Press and hold the #1 on the remote control for about six (6) seconds or until the relay clicks or the control engine light flashes once on the dash. Release button #1, press and release the button #1 again. The relay or check the engine light on the dash flashes twice. The drive is now scheduled for the TACH option. Press and release the #1 again, the relay clicks, or the control engine light on the dash flashes once. The unit is scheduled to select a return to TACHLESS. NOTE: The factory setting is the Tachless option. RED In +12V Fixed BLACK LIGHT COFFEE (-) Parking light output (Requires optional part #775) BLUE/BLACK (+) BRAKE SWITCH KITRINO/BLACK BLUE ENTRY (-) Aux. BLACK/BLUE alarm channel input (-) To cover the BLACK/WHITE tach switch to (-) Neg. Side of the RED/BLACK coil (-) GRAY Shutdown Alarm Factory (Not used) KITRINA KERA Hold as straight as possible, the end of the tape to keep straight. WHITE Or white cable in ignition 1. If your white car has 2 gleties, use both. RED FUSE All red cables need a constant +12V. RED KITRINE/BLACK POWER on a start/turn cable on accessories wires operated by the white/BLACK heater/blower machine. Connect only the ignition switch cable belt. MECHANICAL SAFETY SWITCH When installing a Bulldog telescope on GM or Dodge Dakotas vehicles built before 1996, you must: Use the diagram below to create a circuit that will prevent the remote starter from starting the vehicle unless the key has been removed from the ignition switch. PRE-1996 GM REAR WHEELS WITH PURPLE CRANK WIRE Optional part #775 required. Door switch driver TAN Ground Key Cylinder GREEN Message Center or key buzzer PRE-1996 DODGE DAKOTAS Optional part #775 required. BLACK/LT driver door switch. BLUE Ground Key Roller LT. BLUE/GREEN Message Center or Key Buzzer KITRINO WHITE 87 Tie in 86 heavy white fuse 87a cable to safety 4-relay 5 amp strap 30 BLUE (-) Negative hood pin cable DO NOT USE RED CALHAM, MAGNETIZE FROM KITRINO WHITE 87 Draw to 86 heavy white fuse 87a cable 4-relay 5 Amp safety wires 30 BLUE (-) Negative wire hood pin DO NOT USE RED COVER, MAGNETIA FROM THE BLACK RED 85 85			