Kantech ktes installation manual

I'm not robot
reCAPTCHA

Continue

1 The main advantages of 3 EntraPass Guide and Reference System... 6Strion 6 out of 601Instruction in the Purpose Workspace installation (Workspace section)..... .. The purpose of message management settings... .. Appointment of alarm management settings Alarms) Appointment of network alarms (NetworkTrad 7 of 601Instruction in installation Appointment relays and inputs . Page 8 of 601Instruction in the setting of appointment events to record by camera .. The appointment of Tamper and the problem (Tamper and Trouble)... The purpose of the entrance for the elevator cabin..... . 225 Order of Choice of 226 Establishing the camera's connection to the 227Strion 9 out of 601 Installation instructions Elevator door restart schedule Events and Hours for Camera Recording..... .. 268 Allowing access to the elevator floor. 268 Denying access to the ground from elevatorStrion 10 of 601Instruction in installation Adding text objects Add barcodes Change barcode properties Page 11 of 601Installation destruction for the operator with read-only access

. 424 The purpose of the components of the panel 424 Target EventsTraster 13 out of 601Information in the installation of the choice and configuration of the report printer (report printer) 475 Choosing and Configuring the Electronic Printer Pass (Badge Printer)......badges).............. Changing the system date and time... .. 476 ConfigurationStrion 14 out of 601Installation Update Database Fields (Update Database Fields)... Checking the arraric structure of the database Strion 15 of 601The installation instruction Chapter 1: Introduction Congratulations on purchasing the EntraPass software package, a highly efficient multiplayer access management system? What is an access .. Checking the Link Database (Verifying Database Links)..... control system? The access control system is a complex of compatible technical means (readers, Properly installed Pass sensors, motion detectors, etc.) and 17 out of 601 Electronic PagesInstallation The main benefits of the DePass Kantech Advantage Program (KAP): Activating the software layout provides you with a free 12-month upgrade and the ability to undergo online training by the end of page 18 of 601 Instruct to install additional equipment. Allows chain connection to 16 KT-MOD-OUT16 modules for each KT-400 controller, i.e. up to 256 external outputs. Kantech Telephone System (Kantech Door System) KTES is able to provide access to the buildingTrad 19 of 601 Instruction in the establishment of situations where necessary location of all people in the areas. The system knows how many people are in a given area. Muster reports are printed automatically or in an alarming event. The area icon on the desktop is changing dynamically, page 20 of the 601 Identification Guide and the Reference System EntraPass Usage Reference Guide are designed for installation specialists, system administrators, and EnterPass system administrators, and electronic version of page 21 of 601 Inst of Installation Technical Support If you could not find an answer to your question in this guide or in the reference system administrators, and EnterPass system administrators, and electronic version of page 21 of 601 Inst of Installation Technical Support If you could not find an answer to your question in this guide or in the reference system administrators, and EnterPass system administrators. For page 22 of 601 Instruction in system graph installation 8 1 q :Introduction 8 1 q :Introduction Page 23 of 601 Instructions to installed in the same way as Software Forward 24 of 601 Installation, the recommended system requirements listed below are true for the primary server and backup entraPass, Video Vault video storage, Oracle/MS-S'S (Card Gateway), Windows Gateway), Windows Gateway, SmartLink interface, and workstation. Make sure that the 25-part 601Struction installation Requirements For various tasks may require the following equipment: q Plate for scanning images - allows you to digitize photos of users and use them for identification Requirements For various tasks may require the following equipment: q Plate for scanning images - allows you to digitize photos of users and use them for identification Requirements For various tasks may require the following equipment: q Plate for scanning images - allows you to digitize photos of users and use them for identification Requirements For various tasks may require the following equipment: q Plate for scanning images - allows you to digitize photos of users and use them for identification Requirements For various tasks may require the following equipment: q Plate for scanning images - allows you to digitize photos of users and use them for identification Requirements For various tasks may require the following equipment: q Plate for scanning images - allows you to digitize photos of users and use them for identification Requirements For various tasks may require the following equipment: q Plate for scanning images - allows you to digitize photos of users and users includes a CBLK-10 kit consisting of a 30 meter RS-232 cable with RJ-12 connectors, as well as DB9F-12X 27 601Instruction you must ensuallation of installation pricedure Sheet Page 1- Installation of installation of installation of installation of installation scenarios. Table 2-1 shows different installation of installation scenarios. Table 2-1 shows different installation of i that no EnPasstra application is currently running. Install a CD on your computer software installation process. The Configuration Start window opens. 6 Here you must choose which system components to install a CD on your computer software installation process. The Configuration Start window opens. 6 Here you must choose which system components to install a CD on your computer software installation process. The Configuration Start window opens. 6 Here you must choose which system components to install a CD on your computer software installation process. The Configuration Start window opens. 6 Here you must choose which system components to install a CD on your computer software installation process. The Configuration startup, SetupStructions in install a CD on your computer software installation process. The Configuration startup, SetupStruction in the installation of 7 Push Next to continue working. The Serial Number window opens. 8 Number Global Server or EntraPass Software. This information will become a 31-of-601Instruction by installing 11 Click Next to continue working. The Next button will become a 31-of-601Instruction by installing 11 Click Next to continue working. The Next button will become a 31-of-601Instruction by installing 11 Click Next to continue working. The Next button will become a 31-of-601Instruction by installing 11 Click Next to continue working. The Next button will become a 31-of-601Instruction by installing 11 Click Next to continue working. The Next button will become a 31-of-601Instruction by installing 11 Click Next to continue working. The Next button will be not a serious because of the Next button will be not a serious because of the Next button will be not a serious between the Next button will be not a serious between the Next button will be not a serious between the Next button will be not a serious between the Next button will be not a serious between the Next button will be not a serious between the Next button will be not a serious between the Next button will be not a ser 601 Instruction in installation 15 16 17 18 19 20 q The user can choose the default path and click Next or indicate another path. To specify a different way to install the application, click Change. In this case, a new window opens, in which you need to specify a different form of installation. Page 33 of 601 Instrucciones is automatically activated when the system is loaded, even if the last shutdown was incorrect. 22 Press Next to continue working. The system will check if other applications or utilities are available to install. When found, 34 of the 601 Installation 25 will appear on the screen to complete the installation to press Finish. NOTE: After the installation to press Finish with the program as quickly as possible so that users can install additional options and work with the program. without restrictions. In fact, the system works even without but in the truncated version, page 36 of 601Instruction in installation in programs I am 24 and stands out in yellow). System registry. 4 Open the window Press the yellow Temporary Password button in use (...) (use a temporary password) to register the system registry. 4 Open the window Press the yellow Temporary Password button. NOTE: If you are not already a member of the company, confirm your desire to become one and wait for an email confirming that it is included in the partner list (1-2 business days). 6 Select Section 38 of 601 Installation Information 1 In the main server window (Server) open the Connection menu (or in the Application window of type Workstation enter the Options menu, (Server) open the Connection menu (Server) open the Connection menu (or in the partner list (1-2 business days). with local page 40 of 601 Installation 9 Repeat steps 3 through 8 for all system components. NOTE: You must establish a connection between the entraPass server and the computer, be quickly identified. You can also rename applications as desired, ensuring that events on the system are quickly identified. You can also rename the components in the description menu of these components: DevicesStrion 42 of 601 Instruction to installed on the computer and to find out, it's usually enough to click on the rolled VPN icon in the lower-right corner of the screen next to the clock (the so-called trey). In the Authentication password field, you can specify a specific password that will use the 44XtraXTrax installation instruction to install the internal global gateway (NCC8000) on Windows® 98, the EntraPass application, and the gateway can be installed on a computer. In this case, the following lines reflect the Config.sys file. Edit Config.sys file. Edit Config.sys 1 2 3 4 Select the Windows Start/Start menu. Select A 45 out of 601Instruction to install the external global gateway (NCC8000) in the global gateway is installed on another computer that does not have a gateway (NCC8000) To configure/connect the external global gateway (NCC8000) To configure the external global gateway (NCC8000) To configure/connect the ext Program (EnterPass. 2 Customization Program In the Device Table), Page 47 of 601Instrucciones 4 Go to www.kantech.com and click Member Center. NOTE: If you are not already authorized to the member center, please leave your application on the site. Update While the system load is close to zero (for example, Saturday night). The Configuration Start window opens. 4 Highlight Update Installed Applications and click Next. The Software window above will include a list of all programs, Page 50 of 601 Instruction when installing 5 Click Next to continue working. An update starts and all programs installed on this computer will be updated up to this point. 6 To read the Read-Me introductory file, which contains information about updates made for different applications, click Finish. NOTE: After the upgrade is complete, you must restart the computer in the sequence described at the beginning of this chapter, see Before upgrading EntraPass on page 34. 37Station 52 of 601Instruction in installation remove the EntraPass If you need to remove the EntraPass software from your computer, you will use the Add or Remove Programs option in Control Panel. 1 2 Click Start > Settings > Control Panel. At opening 53 of the 601Instruction in installation removal software from your computer, you will use the Add or Remove Programs option in Control Panel. 1 2 Click Start > Settings > Control Panel. 1 2 Click Start > Settings &g 39 Removing the EnterPass Software Page 54 of 601 Installation Information Chapter 3: Introduction This section introduces users to the graphical user interface and basic functions of the EntraPass System. To log in to EntraPass server, the EntraPass server, the EntraPass Software Page 54 of 601 Instruction Work Company when you install Login and End of Session 1 To enter the Windows Start menu® and open Start > All Programs (All Programs) > Global Step Edition > Server/Workstation). As an EntraPass application, you can use the 601Instruction WorkStation 56 to install 3 To press the Sign In/Sign Out button to open the operator registration. When the desired menu item to perform the necessary actions or display system information. NOTE: The status line shows a function window. By default, kantech is used as the user name and password in the desired menu item to perform the necessary actions or display system information. NOTE: The status line shows a function of the operator registration window. By default password in the desired menu item to perform the name is not sensitive to registration. the status of the connection: Green means that the link is in order, red indicates communication problems. 6 Enter the cursor in statusstcheckStrage 58 of 601Information data received from server 59 of 601Installation 2 The main window of the EntraPass Workstation program appears on the screen. NOTE: If the server is not connected, the extreme left status indicator (all status indicators are colored rectangles on the status indicators are colored rectangles on the sextings (Caps Lock button). To resize toolbar buttons, page 62 of 601 Installation Instructions Automatic Installation (Express Settings) Express Settings) Express Settings allows you to configure settings for system components, including sites/beams/branch controllers and controllers and controllers, as well as devices associated with these components (e.g. doors and entries). allows you to perform a variety of tasks, including checking system databases and changing the interface language. Here's what following buttons. setting the default settings. The System Tree View button displays devices in an erhaic format. Components, Page 66 of 601 Installation destruction Basic features List the main actions available when working on the system: Find components, Extended selection box) - Selection of components, Extended selection box - Selection box - Selection of components, Extended selection box - S a search button with a binocular image and a plus sign. 4 5 To cancel the search on page 68 of 601Instruction in the installation (Delete All). To return to the previous menu screen unchanged and without highlighting, click the Cancel button. 5 There is another way to highlight, which is illustrated by the component selection example in the Controller Status window. ItStrion 70 out of 601 Installation of a print report or a report or list save list for later viewing through the Quick Viewer program or downloading an already created report. For more information about this program, see Chapter 16 of 'The Quick Viewer - Qu System Tree View mode, you can double-click to select a component. The changes will take effect automatically. Click on the 74th Installing Additional Window Usage 1 From the System Devices Toolbar After installation of the computer and software system equipment must be configured. On the Devices tab, located in the ARM panel, you can access the 601Instruction for DePass software package configuration by installing the Minimum EntraPass Application can be integrated with page 77 of 601Instruction in the 3 4 5 Dual Gateways installation, included in the Global Gateway windows, which allows you to simultaneously run global and corporate gateways at the same time. This option only adds a corporate gateway and does not require an additional license. Provide a name for the 78 of 601Installation. Choose this option, the system will automatically prohibit the 79-out-of-601 Installation Instruction, which allows you to create geographic links in the EntraPass system. describe how the workstation should work. ••• Applying the workstation workspace and event parameters allow you to apply the ARM workspace and event parameters allow you to apply the workstation must be Send message at confirmation timeout option if, after the time expires, page 83 of 601Instruction when installing 1 Open Email tab in the EntraPass application. 2 In the Email server (SMTP or Exchange server) box, specify the IP address of the mail server to use to send emails. In the E-mail port box, specify the IP address of the mail server to use to send emails. In the Email server to use to send emails. In the EntraPass application. 2 In the Email server to use to send emails. In the EntraPass application. 2 In the Email server to use to send emails. In the Email server (SMTP or Exchange server) box, specify the IP address of the mail server to use to send emails. In the Email server to use to send emails. In the Email server to use to send emails. In the Email server to use to send emails. In the Email server to use to send emails. In the Email server to use to send emails. In the Email server to use to send emails. databases (map table, map table, map table, map table, map table, and map table, and map table). 85 of the 601 installation instruction 86 of 601 is in effect for the oracle/MS-S-SL interface, enter the domain name and user name in the login name. Enter on S'L server, or S'L server, or S'L server, or S'L server or S'L server, or S'L server or S'L server, or S'L server or S'L se the password in the Password box and repeat your entry in the password confirmation box. Create server databases manually To integrate the database and backup server. To configure the ARM workstation to work with a mirrored base and page 88 of 601 Information in the INSTALLATION NOTE: If you select the TCP/IP protocol, the redundant server address appears on the screen, where you must specify the TCP/IP address of the computer on which the mirror base and backup server are installation instruction 89 of 601 11 Move to the KT-NCC tab to assign a public IP address or domain name. 12 Click ServiceTraTrackets of the computer on which the mirror base and backup server are installed. This field also appears when you use installation instruction 89 of 601 11 Move to the KT-NCC tab to assign a public IP address or domain name. 12 Click ServiceTraTrackets 90 of 601 Instruction 1 In the Drop list EntraPass application choose the SmartLink application. 2 Configure the ARM on which it is installed SmartLink workstation). Highlighting this option prevents unnecessary commands and reporting events that are not designed for the SmartLink application. NOTE: You must manually page 92 of 601Installation 13 Open the Service Marker (Service) and configure the necessary parameters to log in when you use the SmartLink server in service mode and the necessary parameters to log in when you use the SmartLink server in service mode and the name structure. The settings in this window reflect how videos should be displayed in the video store (video > browse the video store). Target drive(s) (disk destination): List 94 of 601Instruction in the installation of note formats: KVI and KVA allow users to protect video file swith a password and specify keyframes for any dedicated video event. Keyframes provide a quick search for video clips by viewing individual frames. Imp selected as ASterer 96 of 601 instruction to installation 8 Significant frame in sequence (keyframe using sequence). This feature is only used with vaulted cameras that are tuned to a specific preposition or autotour path, which requires a 97 of 601 instruction to install the Entrapass Gateways gateway configuration to convert the information received from a controller or site and transmit the converted data to the server. Gateways also convert information received from the Gateway drop-down list, specify the gateway transmit it to controllers. The Gateway transmit it to controllers. The Gateway option was allowed in the Global Gateway application, 99 out of 601 Installation 4 Open Dialer KT-100/KT-200/KT-300 Events (Events KT-100/KT-200/KT-300) and set the on (off) event timer for each. The Corporate Gateway version allows you to configure up to 30 events in this way. 5 See the KT-400st 100 of 601 Instruction in installation 6 On the KTES events), turn on the switch and turn off the edit LED (Press off) for each event. NOTE: The Corporate Gateway application supports up to 41 gateways. 88 4 System Devices Page 101 of 601 Instructions in installation in instructions Below are all the events allowed on the corporate gateway: Access granted (access granted (access granted) Request for assembly denied (Request for prohibited protection) Timeout waiting for a second card (Timeout waiting for the second card) 102 out of 601 Instault information 7 Low keyboard delays) configure the reader keyboard delays (keyboard delays) to fee on the second card (Timeout waiting for a second card) 102 out of 601 Instault information 7 Low keyboard delays) configure the reader keyboard delays (keyboard delays) configure the reader keyboard delays) (access granted) 102 out of 601 Instault information 7 Low keyboard delays) (access granted) 102 out of 601 Instault information 7 Low keyboard delays) (access granted) 103 of 601 Instault information 7 Low keyboard delays) (access granted) 103 of 601 Instault information 7 Low keyboard delays) (access granted) 103 of 601 Instault information 7 Low keyboard delays) (access granted) 103 of 601 Instault information 7 Low keyboard delays) (access granted) 103 of 601 Instault information 7 Low keyboard delays) (access granted) 103 of 601 Instault information 7 Low keyboard delays) (access granted) 103 of 601 Instault information 7 Low keyboard delays) (access granted) 103 of 601 Instault information 7 Low keyboard delays) (access granted) 103 of 601 Instault information 7 Low keyboard delays) (access granted) 103 of 601 Instault information 7 Low keyboard delays) (access granted) 103 of 601 Instault information 7 Low keyboard delays) (access granted) 103 of 601 Instault information 7 Low keyboard delays) (access granted) 103 of 601 Instault information 7 Low keyboard delays) (access granted) 103 of 601 Instault information 7 Low keyboard delays) (access granted) 103 of 601 Instault information 7 Low keyboard delays) (access granted) 103 of 601 Instault information 7 Low keyboard delays) (access granted) 103 of 601 Instault information 7 Low keyboard delays) (access granted) 103 of 601 Instault information 7 Low keyboard delays) (access granted) 103 of 601 Instault information 7 Low keyboard del the NCC-8000 gateway that you want to configure. 2 On the General tab: Use the down/top keys to indicate the number of rays that are dentin to that computer (maximum 8). NOTE: On the Same PC on which the other gateway, in RayTrad 104 of 601Instruction in Installation 4 If the NCC-8000 is integrated into the gateway, in RayTrad 104 of 601Instruction in Installation 4 If the NCC-8000 is integrated into the gateway, in RayTrad 104 of 601Instruction in Installation 4 If the NCC-8000 is integrated into the gateway, in RayTrad 104 of 601Instruction in Installation 4 If the NCC-8000 is integrated into the gateway, in RayTrad 104 of 601Instruction in Installation 4 If the NCC-8000 is integrated into the gateway (NCC-8000 is integrated into the gateway (NCC-8000 is integrated into the gateway). Gateway, configure Stalk 105 from 601 Instruct to Set Up Global Gateway 1 2 From Devices Tab, click the Gateway icon. In the Gateway icon. In the Gateway icon. In the General tab: Use up/down valves to select Page number 106 of 601 Installation 5 Go to the Events tab KT-400. The following table lists all events, page 107 of 601 Installation 5 Go to the Events KT-400. The following table lists all events KT-400. The following table lists all events KT-400 (Events KT-400). Global Gateway icon. In the Gateway reader keyboard: Delay between digits (delay between tigits (delay between two consecutive keystrokes, min:sec). This is the maximum time allowed Frad 108 of 601 Instruction in the installation Manual, DN1656. WAN: Use this type of connection to KT-NCC Quick Setup Guide, DN1656. WAN: Use this type of connection to KT-NCC Installation Manual, DN1611 and KT-NCC Quick Setup Guide, DN1656. WAN: Use this type of connection to be surrounded by distant objects. When the connection to KT-NCC Installation Manual, DN1611 and KT-NCC Quick Setup Guide, DN1656. WAN: Use this type of connection to KT-NCC Quick Setup Guide, DN1656. WAN: Use this type of connection to Manual, DN1611 and KT-NCC Quick Setup Guide, DN1656. WAN: Use this type of connection to be surrounded by distant objects. address can be found on the KT-NCC card, under the Ethernet port #1. This is a 12-digit 16-digit code where every two digits are separated by a trait. (xx-xx-xx-xx-xx). The following table shows what settings to specify based on networkStrivet 110 of the 601Instruction in Network Response Time) installation is set by default. You can change the survey time between EntraPass and KT-NCC. Communication time/Communication time/Comm standby time: max. 1500 msTrastra 111 of 601Installation 6 Rest assured that the item is selected: Allow KT-Finder diagnostic access for KT-NCC (allow diagnosing KT-NCC with KT-Finder service). Choose the activation condition for each local relay on the board under Event Activation (Press off) the LED press for each event. KT-NCC (allow diagnosing KT-NCC with KT-Finder service). Choose the activation condition for each local relay on the board under Event Activation (Press off) the LED press for Expression (Expression for Expression for Exp customize related events in this way. The following table lists all available events Instrway 113 of 601Instruction 9 Under Keyboard delays (keystroke delays) to configure keyboard delays (keystroke delays) to configure keyboard delays (stroke delays) to configure keyboard delays (by the walue of the Between Digits option (Delay between two consecutive keystrokes, min:sec). This maximum allowable time after 114 of the 601Instruction in the installation of The Ray Settings (loops) Beam consists of drivers connected to the same sequential port. This system can control up to 32 local beams on the corporate gateway, and 32 beams on the corporate gateway, 8 beams on the NCC-8000 gateway, 8 physical direct beams on on the KT-NCC gateway, and 32 beams on the controllers. Up to 32 controllers can be connected to each beam. When you enter a value that exceeds page 115 of 601 Installation 4 Under the general options) make the following adjustments: In the Hardware Definition and KTES (Computer Description and KTES) section indicate the number of beams on the controllers. Up to 32 controllers can be connected to each beam. customize security settings and communication settings and communication settings. Encryption key. This field must be entered sixteenth code to protect the beam communicates with the gateway through the terminal server using the TCP protocol. Click the Recover Site Events button (ExtractStrua 121 from 601 Inst installation) This setting will be useful if the primary modem is busy or cannot accept the call. inform them of permission/denial of access. Typically, the reader and button panel installed in this driver from the Reader list drop-down list driver without removing it from the system (for example, for repairs). In addition, it allows operators to easily customize the system uses the correct value above. In the Keyboard Escape Keys (ESC) drop-down list, specify which 128 of the 601 installation instructions are used as a relay. In total, only 16 relays can be configured. If two REB-8 modules are added, the last two relays (17 and 18o) can be used to perform different actions. The various uses of the KT-2252 lift controllers are presented below in the table: Number of floors, Page 130 of 601Instruction in the installation of 2 Open Lay-book (Lift) elevators to configure REB-8 elevator drivers. supports up to four REB-8 modules. 3 Specify how many REB-8 modules are installed in the driver. These options add up. If, for example, four REB-8 modules are installed, the first three lines of The 131 of 601Instruction are installed when installing 1 open KT-2252 elevator controller and the REB8 relay option (KT-2252 and 132 lift controller of 601Installation 1 From the Site menu (Ray) to click the controller icon, select the KT-300 tab. 2 In the Serial number field enter the serial number of the controller, lon this field, only the numbers must be specified, except on the first page 133 of the 601Instruction when installing Combus terminals are marked with flags/red marks. (at the bottom of the screen). in response to a power failure, a Combus error and a low stage 135 of 601Instruction when installing Combus terminals are marked with flags/red marks. (at the bottom of the screen). in response to a power failure, a Combus error and select the reader types box. 2 Specify the type of button panel in the Keyboard Type box (if available). 3 Open the KT-400 marker. In the Serial number field, type the value 136-of-601Struction in installation 1 If the KPyboard escape key (ESC) specifies which button panel key will be used as an AN ESC. This feature is linked to page 137 of 601Installation 1 If the KT-400 marker. In the Grop-down list, the keyboard escape key (ESC) specifies which button panel key will be used as an AN ESC. This feature is linked to page 137 of 601Installation 1 If the KT-400 marker. In the Serial number field, type the value 136-of-601Struction in installation 5 6. This feature is used in high-security areas where two cards are required to access access. In the Arron of the KT-400 marker. In the Serial number field, type the value 136-of-601Struction in installation 5 6. This feature is linked to page 137 of 601Installation 1 If the KT-400 marker. In the Serial number field, type the value 136-of-601Struction in installation 5 6. This feature is linked to page 137 of 601Installation 1 If the KT-400 marker. In the Serial number field, type the value 136-of-601Struction in installation 1 If the KT-400 marker. In the Serial number field, type the value 136-of-601Struction in installation 1 If the KT-400 marker. In the Serial number field, type the value 136-of-601Struction in installation 1 If the KT-400 marker. In the Serial number field, type the value 136-of-601Struction in installation 1 If the KT-400 marker. In the Serial number field, type the value 136-of-601Struction 1 If the KT-400 marker. In the Serial number field, type the value 136-of-601Struction 1 If the KT-400 marker. In the Serial number field, type the value 136-of-601Struction 1 If the Serial number field, type the value 136-of-601Struction 1 If the Serial number field in expansion module configuration button. This opens the expansion modules configuration window. . If you want to configure statement 138 of 601 to installation sample destination outputs 1-8 as sample outputs of output relays 9-16 as lift outputs 6 To adv KT Module-MOD-REL8 You must select the output module and press the Add button. Page 140 of 601Information when setting Sample relay destination 1-8 as relay (relay) (Relays) WARNING! To date, KT-400 controllers are available from 4 relays would be needed to make part of it a 141-of-601Instruction in the installation of 7 Open Summary Bookmark (Common), which allows you to change any configuration used to make part of it a 141-of-601Instruction in the installation of 7 Open Summary Bookmark (Common), which allows you to change any configuration used to make part of it a 141-of-601Instruction in the installation of 7 Open Summary Bookmark (Common), which allows you to change any configuration used to make part of it a 141-of-601Instruction in the installation of 7 Open Summary Bookmark (Common), which allows you to change any configuration used to make part of it a 141-of-601Instruction in the installation of 7 Open Summary Bookmark (Common), which allows you to change any configuration used to make part of it a 141-of-601Instruction in the installation of 7 Open Summary Bookmark (Common), which allows you to change any configuration used to make part of it a 141-of-601Instruction in the installation of 7 Open Summary Bookmark (Common), which allows you to change any configuration used to make part of its angle of the installation of 7 Open Summary Bookmark (Common), which allows you to change any configuration used to be a summary of 7 Open Summary Bookmark (Common), which allows you to change any configuration used to be a summary of 8 Open Summary Bookmark (Common), which allows you to change any configuration used to be a summary of 8 Open Summary Bookmark (Common), which allows you to change any configuration used to be a summary of 8 Open Summary Bookmark (Common), which allows you to be a summary Bookmark (Common), which allows you to be a summary Bookmark (Common), which allows you to be a summary Bookmark (Common), which allows you to be a summary Bookmark (Common), which allows you to be a summary Bookm the modules. Identify the module you want to change in the left column and change in expansion module 8 already installation of the function of preventing rea through the input/output readers. Helps security administrators track the number of 143 out of 601 Installation 5In the Forgive Schedule section to press the dot button to configure a reset schedule on all other cards. Specify the time when the anti-rescue will not work. NOTE: Forgive Schedule Strion modules are configured as input or output for elevators. For more information, see Chapter 4 of Configuration 145 of the 601 Overflow Information and a list of events that occurred when the handler did not communicate with the server. In the example illustrated above, the dedicated Event buffer overflow error message is 50 of the oldest events 601 Kantech Telephone Entry System (KTES) is a telephone system. This is the maximum talk time in seconds for a normal call between a visitor and a tenant (10 seconds to 59 minutes:59 seconds). The default value is 40 seconds. Extended Talk Time: This is the maximum 148 out of 601Instruction in the Kantech Phone Input System 1 2 installation appointment From the KTES window, select the Kantech Phone Input System 1 2 installation appointment From the KTES window, select the Kantech Telephone Entry System 1 2 installation appointment From the KTES window, select the Kantech Telephone Entry System 1 2 installation appointment From the KTES window, select the Kantech Telephone Entry System 1 2 installation appointment From the KTES window, select the Kantech Telephone Entry System 1 2 installation appointment From the KTES window, select the Kantech Telephone Entry System 1 2 installation appointment From the KTES window, select the Kantech Telephone Entry System 1 2 installation appointment From the KTES window, select the Kantech Telephone Entry System 1 2 installation appointment From the KTES window, select the Kantech Telephone Entry System 1 2 installation appointment From the KTES window, select the KTES window is a select t 149 of 601 Instruction in the installation of the keyboard key for the tenant-activated auxiliary relay (The key that activates the additional relay with the help of the tenant): This key will be used to provide access to the visitor's territory if the second entry is used. The default value is empty. Include the 150 of 601 Instruction in the installation of special symbols with a combination of special symbo format: Page 151 of 601In the character delay: Next character delay: Next character delay is the maximum delay that occurs when the next digit occurs when t next digit is indicated when the next digit occurs when the next digit is entered when there is a KTES input AC power failure. There is no default, 2 seconds. Look for user timeout delay: After clicking page 152 of 601Instruction on power failure installation: This relay can be activated when there is a KTES input AC power failure installation in i are installed. Any door can be an elevator door, a working time gate, a front door with a re-ban of 156 out of 601 Instruction in the elevator cabin option if the door is used in the elevator cabin option if the door is used in the elevator cabin option if the door is used in the elevator door, a working time gate, a front door with a re-ban of 156 out of 601 Instruction in facility 5 6 If this door belongs to KTES then go to point 13. Check the Elevator cabin option if the door is used in the elevator cabin option if the door is used in the elevator tab to configure 157 of the 601 Instruction in the installation of the opening duration (h:mm:s). correctly or a correct exit request. This function only applies to doors equipped with contact sensors. TimeStrion 158 out of 601 Installation 1 In the door window (Doors) open the keyboard (working code). 2 Specify how the door, for example: break the door, for example break the door, for example break the door, for example break the door, leave the door open for too long, the function of mutual locking of the door (Door) and another 1 In the door window (Doors) open the REX tab (Output Request Devices) and in the Relock on Rex section (lock on REX signal...) choose the necessary locking functions In the door opening - to allow the system to turn on the lock after opening the door correctly Strivestre 161 of 601 Instruction in the installation of NOTE: The Door option does not apply to KTES doors. 1 In the Door window) open the Elevator marker. 2 From the Door (Doors) drop-down list, choose the first door to use in the mutual door locking system (Gateway). In the Door window (Doors) open the Elevator marker. 2 From the Door window) open the Elevator marker. 2 From the Door window (Doors) drop-down list, choose the first door to use in the Door window (Doors) open the Elevator marker. 2 From the Door window (Doors) drop-down list, choose the first door to use in the Door window) open the Elevator marker. 2 From the Door window (Doors) drop-down list, choose the first door to use in the Door window (Doors) drop-down list, choose the first door to use in the Door window (Doors) drop-down list, choose the first door to use in the Door window (Doors) drop-down list, choose the first door to use in the Door window (Doors) drop-down list, choose the first door to use in the Door window (Doors) drop-down list, choose the first door to use in the Door window (Doors) drop-down list, choose the first door to use in the Door window (Doors) drop-down list, choose the first door to use in the Door window (Doors) drop-down list, choose the first door to use in the Door window (Doors) drop-down list, choose the first door to use in the Door window (Doors) drop-down list. (Definition menu), Page 163 of 601 Installation 1 Use the Access and Area tab to determine the entry by two maps, the before/after area, and restrictions for assigned doors. 2 Highlight dual custody (two-card pass) to enable this feature. Double custody is used for A.I.O. 164 of the 601 Instruction in the installation of NOTE: When the cardholder brings his/her cards to this cardholder, it is not possible to bring his/her cards to readers/doors until the specified time delay expires. Door, another gate event setting the cards to readers/doors until the specified time delay expires. (Door Events section) (corporate gateway only) 1 VStrage 165 out of 601Instruction to install two different groups of uncasts for each event, you must include page 174. Don't call type (page call type applicable only to KTES): You can choose Do not call, (do not call, Local relay activation will not cause a call to be sent to the pager), Call Immediately (Call Immediately. Activation of the local relay will be activated (the lock will be activated the lock will be activated (the loc able to put in the protection of the external security panel. To increase safety, 169 of the 601Instruction in installation relay weekend relay of weekend relay of weekend relay of the postponed arm 10Stration 170 of 601Instruction in the installation relay installation relay weekend relay of weekend relay of weekend relay of weekend relay of weekend relay for deferred safety in the protection of the external security panel. To increase safety, 169 of the 601Instruction in installation relay weekend relay of we managers, They are equipped with each KT-100, KT-200, KT-300 and KT400 controller, can be used to trigger alarms and other devices, including lighting regulators, ventilation systems and air conditioning. These 171 of 601 RelaysInstruction in installation 7 Under the NCC-8000 gateway, you must assign the activation program activation program activation program activation program activation program activation program activation program. (manual control, Page 172 of 601 Insection to install the input configuration (section input) Door controllers monitor the flow of inputs/input state: closed or sensors, temperature sensors, temperature sensors that open doors, locks, motion detectors, temperature sensors of the door or sensor Output Request Buttons (REX), and other devices with dry page 173 of 601 Instruction in the installation: Input used for the door or sensor Output Request Buttons (REX), and other devices with dry page 173 of 601 Instruction in the installation: Input used for the door or sensor Output Request Buttons (REX), and other devices with dry page 173 of 601 Instruction in the installation: Input used for the door or sensor Output Request Buttons (REX), and other devices with dry page 173 of 601 Instruction in the installation: Input used for the door or sensor Output Request Buttons (REX), and other devices with dry page 173 of 601 Instruction in the installation: Input used for the door or sensor Output Request Buttons (REX) and other devices with dry page 173 of 601 Instruction in the installation: Input used for the door or sensor Output Request Buttons (REX) and other devices with dry page 173 of 601 Instruction in the installation in the i open. NOTE: When using page 174 of 601 Information in the INSTALLATION NOTE: To indicate the type of call for the pager also return to normal. The system will form page 176 of the 601Instruction in the installation of THE NOTE: Only those floors that are marked (X) with a flag in the Floor Group menu, the Status column will be available for select the Door tab. 2 3 Select the Door tab. 2 3 Select the Door tab. 2 3 Select the door group, which will be unlocked by alarm at the input/entry. Select the action you will follow after unlocking the doors q Latch (lock) will keep the unlocked doors up to 178 of the 601Instruction to install the outputs (four for one door). KT-100Strage 179 of 601Instruction to establish door event connections with additional system event outputs can trigger additional outputs. To do this, you must specify how each event should trigger a custom output. 1 Open the BookmarkTrad 180 definition of 601Instruction to install the built-in alarm panel Settings Minimum requirements to view and use built-in buttons, see Chapter 14 Integration must be downloaded to EntraPass Server. If the toolbar does not display two buttons, see Chapter 14 Integration must be downloaded to EntraPass Server. If the toolbar does not display two buttons, see Chapter 14 Integration must be downloaded to EntraPass Server. If the toolbar does not display two buttons, see Chapter 14 Integration must be downloaded to EntraPass Server. If the toolbar does not display two buttons, see Chapter 14 Integration must be downloaded to EntraPass Server. If the toolbar does not display two buttons, see Chapter 14 Integration for the Integr you will see the Video View box (ViewTraction 182 of 601Instruction when installing 13 Select COM Communication Port (Com Communication Port) (and Baud Speed (Transfer Speed) from the drop-down list. 14 Select the Info tab (information). This code used by the Kantech operator for channel 183 of 601Instruction when installing 13 Select COM Communication Port (Com Communication Port) (and Baud Speed (Transfer Speed) from the drop-down list. 14 Select the Info tab (information). This code used by the Kantech operator for channel 183 of 601Instruction when installing 13 Select COM Communication Port) (and Baud Speed (Transfer Speed) from the drop-down list. 14 Select the Info tab (information). This code used by the Kantech operator for channel 183 of 601Instruction when installing 13 Select COM Communication Port) (and Baud Speed (Transfer Speed) from the drop-down list. 14 Select the Info tab (information). This code used by the Kantech operator for channel 183 of 601Instruction when installing 13 Select COM Communication Port) (and Baud Speed (Transfer Speed) from the drop-down list. 14 Select the Info tab (information). This code used by the Kantech operator for channel 183 of 601Instruction Port) (and Baud Speed (Transfer Speed) from the drop-down list. 14 Select the Info tab (information). This code used by the Kantech operator for channel 183 of 601Instruction Port (Info tab (Info Installation Configuring Integrated Components on the Integrated Components on the Integrated Component tab (integrated Component tab (integrated component) you can see any of the panel components (section section •• Расписания Тревожная система (Alarm systems) Области Тур обхода охранникомСтраница 185 из 601 Инструкция по установке Назначение расписаний Расписании включая автоматическую разблокировку дверей, предоставление доступа посетителям, создание автоматических отчетов, мониторинг входов и др. ., s, 186 х 601 1 ' 1 ' 1' (Definition). On the Definition toolbar, click Schedules. NOTE: If the flag was placed in front of the Upgrade to Advanced Programmingtrat 187 of 601Instruction capability in the calendar installation for the Purpose of the Alarm System (Global/KT-NCC/NCC 8000) The alarm section (alarm partition) is the assembly of devices and equipment designed to signal and determine presence in the protected area. This reaction involves the immediate participation of the 189-out-of-601Inthuhusstruction in the facility. When disturbing sections, elements such as: doors, readers, input zones and relays that can be assigned to groups and separately. Each disturbing section of 190 of 601Instruction in the facility. When disturbing section of 190 of 601Instruction in the facility. will be protected after the output delay expires. Automatic arming (automatic arming (automatic registration protection): The alarm section will be 191 of the 601Instruction in the installation To assign a disturbing section 1 of the gateway from the drop-down list, selection will be 191 of the 601Instruction in the installation To assign a disturbing section under sediment protection mode, page 192 of 601Installation To assign a disturbing section 1 of the gateway from the drop-down list, selection will be 191 of the system is automatically put on guard only if the unarmed schedule is not included. Can I activate in two cases the procedure of placing a protection mode, page 192 of 601Installation To assign a disturbing section 1 of the gateway from the drop-down list, selection will be 191 of the system is automatically put on guard only if the unarmed schedule is not included. Gateway, which refers to its disruptive section. 2 From the Alarm System drop-down list, select the existing alarm of 601 Instruction in installation 6 B q requires an appropriate level of access to the reader/i. Delays), specify an input delay: Specify an input delay: Specify an input delay during which userTrad 194 of the 601 Security Information will only work with a gun reader. Security requires a level of access to the reader/ii. Delays), specify an input delay: Specify an input delay during which userTrad 194 of the 601 Security Information will only work with a gun reader. security and access to these readers. Note: Alarm level #1 input (Anxiety, Level No.1) - Select an input or group of inputs that will automatically activated in the installation will remain activated until the input/entry changes its state. NOTE: When the relay is a 197

relay of 601Instruction in the installation q q Alarm #1 Relay status - Choose a relay that will be activated when the alarm section detects an alarm at the input, From one or a group of entries identified in the Alarm level #1 field or from one or more gates (for example, forced opening door 198 of 601Instruction when setting area allocation areas (global only/KT-NCC/NCC 8000 Gateway) Areas are a base point for using Anti-passback mode. NCC 8000 featureStrivet 199 of 601Instruction when setting area allocation areas (global only/KT-NCC/NCC 8000 Gateway). function, you will have a video view box (Select video window). Avoid messages like Access Denied - Password Bad Location (Card in a Bad Place). When the trip schedule becomes valid (or invalid), you can specify the area where page 201 of 601Instruction in the Installation Assignment of the graceways/KT-Ng/C/NCC/NCC (Select video window). Avoid messages like Access Denied - Password Bad Location) or Card in Bad Location (Card in a Bad Place). When the trip schedule becomes valid (or invalid), you can specify the area where page 201 of 601Instruction in the Installation Assignment of the prescribed schedule. Stops can also be Astration 202 of 601Instruction in installation 4 5 6 7 When necessary, enter Time Setting based on the gateway time zone (setting the time zone between the server and the gateway). If, for example, you have a time difference of 1 hour and 30 minutes, type 1.5. You can highlight the automatic stop guard path in the 601Instruction 203 ink in The Settings Appointment Floors Floor Menu to create and edit floors for elevators After the creation of floors, they are grouped and tied to the schedule on which access to a particular floor depends. 1 On the Definition (Appointments) toolbar, click Page 204 of 601Instruction in the event/relay link installation appointment (Global/KT-NCC/NCC 8000 gateway only) This menu is designed to communicate events that will trigger the relay. You can also assign that the relay will be activated during a specific schedule. Relay can be activated, Page 205 of 601Instruction in installation Print Event Event (Event Relay) This menu is used to print for a specific event. 1 In the Event Relay window, click Printer. 2 3 4 In the Event (Event) for which you want to print page 206 of 601Instruction in the Graphical Mapping Schemas installation Graphic and to print for a specific event. 1 In the Event Relay pane, select Event (Event) for which you want to print page 206 of 601Instruction in the Graphical Mapping Schemas installation Graphical diagrams, operators can easily identify the exact location of page 207 of 601 Installation Information 4 In the Chart window, 4 In the Chart window, click Click here to create, edit, or modify a chart (Click to create, edit, or modify the option Add live video as background) to add to the live video as background. Highlight the option Add live video as background option to add a web page as a background to add a web page to the background. To do this, in URL 209 of 601 Instruction to install Create a Background Image for a Viewport 1 Double-click the background image in the Assign Components window. 2 Use this window to open the Background Image in the Assign Component links with graphic icons 1 Page 211 of 601 Instruction by Print System Components and Graphics 1 2 From the definition toolbar, click the Chart icon and select the chart icon and select the chart sto print using the windows of your choice. 201 Graphical Appointment Schemas Page 213 of 601 Instruction by Print System Components and Graphics 1 2 From the definition toolbar, click the Print (Print) to send the graphics schema to the printer. 202 5 q: Dating Page 214 of 601 Instruction by Print System Components and Graphics are handled differently than other days. It is recommended to plan the holidays at the beginning of the year; pre-setting holiday with a floating date (Easter, Thanksgiving, etc.). Vacations can be assigned to a specific type (Hol 1, 2, Page 215 of 601Information in The Purpose Task Builder (Team Design) Minimum requirements for task builder (Team Design) Minimum requirements for task builder icons (team designer) and event trigger (event trigger) will be displayed whenever the SmartLink component has been installed on ARM and is registered on the EnPasstra server. Panel 216 of 601Instruction 1 Click the task insertion menu for the SmartLink button/menu will be displayed on the screen. Email Insert email into a task to which Automata is sent when an event occurs. Modem Insert message into a task to which Automata is sent by the integrators in the pager when page 218 of 601Instruction in the Add to Email task 1 installation Once you have created a new task or chosen an existing task, click the Mailbox icon. The Email Task Builder window will be displayed on the screen. 2 3 Enter your email address in the... (From). Enter the email address to which you wantTrad 219 of 601Instruction when installed. Enter the Dial Information section in phone number and transfer rate in the port number and transfer rate in the email address to which you wantTrad 219 of 601Instruction when installed. Enter the Dial Information section in phone number 220 of 601Information in Installed. Enter the Dial Information section in phone number 220 of 601Instruction when installed. Enter the Dial Information section in Installed. Enter the Dial Information in Installed. Enter the Dial Information section in Installed. Enter the Dial Information in Installed. Enter the Dial Information in Installed in Insta tab to view the commands. The port com choice window will appear on the screen in Section 221 of 601Instruction when installing Enter Network Tag) 1 Click the network tag will appear on the screen in Section 221 of 601Instruction when installing Enter the network tag will appear on the screen in Section 23 Enter the network tag will appear on the screen 23 Enter the network tag will appear on the screen in Section 221 of 601Instruction when installing Enter Network Tag (Network Tag) 1 Click the network tag will appear on the screen 23 Enter the network tag will appear on the screen in Section 221 of 601Instruction when installing Enter Network Tag (Network Tag) 1 Click the network Tag (Network Tag) 1 Click are three categories that can be a 223-of-601 Instruction in installation examples Computer type. (Changeable/Build a task with message value variables, which can be linked to the component list. 12 13 Click Points to select a component. Click the points to select an item (which is a 225 out of 601 Information in creating tasks with trigger value variable (a memorable variable (a memorable variable amount) 1234 Click the Definition (Destination in structions 11 In the Trigger Value (remember col. in the task title. Click Points and select the component List Door . 1213 1920 Click Points and select the Task Builder icon. Click Points and select the Commonent List Door . 1213 1920 Click Points and select the Commonent List Door . 1213 1920 Click Points and select the Commonent List Door . 1213 1920 Click Points and select the Commonent List Door . 1213 1920 Click Points and select the Commonent List Door . 1213 1920 Click Points and select the Commonent List Door . 1213 1920 Click Points and Select the Commonent List Door . 1213 1920 Click Points a the trigger action. Page 227 of 601 Installation 22 Click Extended Filter (Advanced Filter (Advanced Filter type. Then select the component filter type. Then select the bottom of the window. Click OK. 7 8 9 The SmartLink task is now displayed in the text box. Save and close Task Builder. On page 229 of 601 Instruction 16 From the list of related events, select the granted access event (access provided). NOTE: Make sure that the User Information to place. You can enter user information field, for example. This box can bestrut 230 of the 601 Instruction in installation Chapter 6 q Integration with ToolBar Video surveillance systems in the configuration of entraPass Global Edition provided the possibility of real-time video surveillance. The 231-of-601Instruction when installing video server connects to the EntraPass system via IP address. The video server configuration (Link), and Event (Events). Open the bookmark to provide log data. 3 Provide the following data: Domain Name . Provide the domain name used by the video server Strion 234 of 601Instruction in the Installation 2 3 Enter the application data enterPass Video Vault This is the name of the EntraPass Video Vault This is the name o schedule settings for the recording camera 1 In the Camera window (surveillance cameras) open the Event (Events) marker. The open list will be displayed with a comment that is entered in this window. 5 Enter a comment in a customizable surveillance camera. Click Save, and then close the window storage in KVI and then close the window. Linking the camera to the icon On the system EntraPass providesStrage 239 of 601Instruction in the installation of The Purpose of VideoView Windows After configuring the video server and assigning cameras, operators can customize the video windows displayed at work CCTV for monitoring and viewing purposes. EntraPass operators can customize the video windows After configuring the video windows displayed at work CCTV for monitoring and viewing purposes. EntraPass operators can customize the video windows After configuring the video windows displayed at work CCTV for monitoring and viewing purposes. EntraPass operators can customize the video windows displayed at work CCTV for monitoring and viewing purposes. EntraPass operators can customize the video windows displayed at work CCTV for monitoring and viewing purposes. EntraPass operators can customize the video windows displayed at work CCTV for monitoring and viewing purposes. EntraPass operators can customize the video windows displayed at work CCTV for monitoring and viewing purposes. EntraPass operators can customize the video windows displayed at work CCTV for monitoring and viewing purposes. EntraPass operators can customize the video windows displayed at work CCTV for monitoring and viewing purposes. EntraPass operators can customize the video windows displayed at work CCTV for monitoring and viewing purposes. percentage of refresh rate is related to image quality/compression. Image quality/compression. Image quality affects the performance of the 241-part 601Instruction in the installation of Create and edit video contract using preinstallation sand traffic routes that allow users to adjust the automatic operation of dome cameras. These options delay, partern display delay. video, transmitted by surveillance cameras, is displayed on the ARM. Pre-configuration of CCTV modes round to video monitoring. Any event associated to video monitoring selected type component can turn logging on and off, including special events, page 245 of 601 Instruction Recording Parameters From the Recording Settings menual for the image selection you must click Test (Check). A custom video window appears on the CCTV desktop dedicated to video monitoring. Any event associated with a selected type component can turn logging on and off, including special events, page 245 of 601 Instruction Recording Parameters From the Recording Settings menual for the image selection you must click Test (Check). A custom video window appears on the CCTV desktop dedicated to video monitoring. allows users to assign video settings and assign a recording source (Intellex, camera to the camera, etc.) and link everything to a specific trigger. For each recording event, you must specify Atram 246 of 601Installation 1 In the recording event, you must specify Atram 246 of 601Installation 1 In the recording event, you must specify Atram 246 of 601Installation 1 In the recording event, you must specify Atram 246 of 601Installation 1 In the recording event. settings, select the Stop Recording trigger (video trigger for recording). Post-alarm recording delay, m:ss (Event Video List) - Allows you to complete recording with some delay after stopping page 248 of 601The list of event shows all video events shows all video events shows all video event List window to click the Search button. Search video events will open. NOTE: If the Legend menu and buttons are not enabled, this window will not display the description and buttons at the bottom. 2 Vinsion 250 out of 601 instruction when you install 7 open Archive State bookmark to filter events using archiving status. 8 Highlight the status of the file if you want to specify which events to list. To include all events, you should not check page 252 of the 601 Instruction counter when you install 1 Select event in the Video event in the Vi Video Playback window. 2 View Camera Marker (Cameras) to view information about cameras that have recorded the 254-of-601Installation of i Key Frame Binding to video event list select event to export button. The Enter a Video recordings Entra Pass users have the ability to save any of the most representative frames of the video event list video File Name window opens. Provide the file name in the file name in the file name. By The file is saved on page 256 of 601Instruction in the play files video playback playback feature allows you to watch a video from any camera at once. To do this, you must specify a time slot to play. The maximum time allowed is one hour. To do this: Select the camera in The 258 of 601Instruction 3In order to save a separate video frame, click Adjust 4 Leave the default name or specify a different name of the stored frame. Image Save Path: Program Server_GE Files To view saved frames, you can use Schedule 259 of the 601Instruction in the Logs installation, the current recording is currently running. This are currently running. rest across an under the reason why the recording is made: The recording starts on page 260 of 601Instruction in the installation of the desktop CCTV bestop Video allows operators to observe in real time the image transmitted by surveillance cameras, connected to the network and configured accordingly. Put on the CCTV window screen 1 Open bookmarks trivet 261 of 601Instruction when installing 4 Click Show View Selector (Call switch to display the View selector window. This small window is used to select the screen break mode when taking images from multiple cameras or when viewing a single camera on a specific path. Page 262 of 601 Instruction in the installation of EntraPass Video Storage View EntraPass Video Storage EntraPass Video Vault provides an easy way to save importan video data for later use. As you know, videos have a limited resource, which depends on the video server configuration and your Page 264 of 601 Instruction in Chapter 7 installation, extended selection box is a window to search for a specific component. The State of the Message Window component, which sucks messages about the gateway, beams, areas, and state of the guard route, can be assigned by right-clicking Action 266 of 601Instruction in the installation The example shown above, the information is displayed for The global gateway. Let's list the basic information that can In this window. Gateway Status Description option shows whether or not the gateway connection to the network. Number of sites Number of in installation Manual gateway control mode with gateway control mode with gateway allows operators to access gateway system allows operators to installation 12 Highlight gateway database and download new data instead. Reloading data from the EntraPass Gateway system allows operators to reload 269 of the 601 Instruction in the installation of beam operations/sites while operations/sites while operations/sites while operating manually, the manual beam/site controller will the site, click the Driver button. This controller will be sent a message requesting identification. Once the controller receives this message from the beam, it will send to ARMTrapment 271 601 MessagesInstruction in driver installation when working manually This menu serves to perform various operations to reset and restart, reload and firmware driver. Soft Reset Description Button -Page 272 of 601Installation -In the Driver list, highlight the driver to work with a controller group, select a group under Controller Group in the lower-right pane. NOTE: If the system is 273 of 601 Installation 1 2 From the Driver menu, highlight the correct driver group. Click the Forgive button on the toolbar. Cardholders inside or outside the status of the doors (one or group). Operators have the ability to manually unlock/lock the door, temporarily lock/remove one or a group of doors, Page 275 of 601Instruction in the door or door group choice installation 1 In the Operation window to click the door status in real time. The left pane displays a list of all 276 of 601Instruction in Installation 1 2 Temporarily click Unlock. A change delay in the action appears on the screen. In the New time box, enter the amount of latency and click OK. The selected door will be temporarily unlocked by Astredive 277 of 601Instruction Elevator door operations when working manually lock/unlock, temporarily unlock floors. This window also displays in real time the evator door in the operation when installing Lift Door Choice 1 In the operation when installing Lift Door Choice 1 In the operation when installing Lift Door Choice 1 In the operation when installing Lift Door Choice 1 In the operation when installing Lift Door Choice 1 In the operation when installing Lift Door Choice 1 In the operation when installing Lift Door Choice 1 In the operation when working manually lock/unlock, temporarily unlock floors. This window also displays in real time the status of the elevator door in real time the operation when installing Lift Door Choice 1 In the operation when working manually lock/unlock, temporarily unlock floors. This window also displays in real time the operation when installing Lift Door Choice 1 In the operation when working manually lock/unlock, temporarily unlock floors. This window also displays in real time the operation when installing Lift Door Choice 1 In the operation when working manually lock/unlock, temporarily unlock floors. This window also displays in real time the operation when installing Lift Door Choice 1 In the operation when working manually lock/unlock, temporarily unlock floors. Once a floor group is assigned, the system will offer the operator to confirm the operator to confirm the operation. Here are the available on/off commands, as well as the temporary activated an entivated and the relay (one or group). This window is also displayed on the activated and the relay (one or group). This window is also displayed on the activated and the relay (one or group). Click Disable Relay. NOTE: If you manually deactivated and the relay (one or group). This window is also displayed on the activated and the relay (one or group). This window is also displayed on the activated and the relay (one or group). This window is also displayed on the activation of the relay (one or group). This window is also displayed on the activation of the relay (one or group). This window is also displayed on the activation of the relay (one or group). This window is also displayed on the activation of the relay (one or group). This window is also displayed on the activation of the relay (one or group). This window is also displayed on the activation of the activation of the activation of the relay (one or group). This window is also displayed on the activation of the relay (one or group). This window is also displayed on the activation of Schedule 282 of 601 Instruction when installing The Input/Inputs operation when working manually This section of the menu allows Enter normality, stop monitor the status of a given entry will return to normal, according to the Settings in the Device menu. Installation 1 2 Highlight the input, monitor the status of a given entry constantly, temporarily deflect the selected entry will return to normal, according to the Settings in the Device menu. Installation 1 2 Highlight the input or group of entries. Click Normal Entry will return to normal, according to the Settings in the Device menu. Installation 1 2 Highlight the input, monitor the status of a given entry will return to normal, according to the Settings in the Device menu. Installation 1 2 Highlight the input or group of entries. Astrive 284 of 601 Instrution when installing manual control over an alarm system after the delay to install Alarm System after. The alarm system can only be used bytre 285 of the 601 Instruction to install place/remove it from the security system after the delay to input. See Chapter 5 in more detail: Destination page 173 1 Select Gateway or Alarm System. 2 Click the DisarmStrund 286 of the 601Instruction in the manual Control with Global Gateway. The ButtonTrap 287 of 601Instruction in the installation of the next bypass destination, and finish the guard route. The Guard route control panel can only be used with Global Gateway. The ButtonTrap 287 of 601Instruction in the installation of the next bypass destination, and finish the guard route. The Guard route control panel can only be used with Global Gateway. element (door or entrance) Bypass. Delay to next station: Displays the time it takes to get to the next point. If this is a 288 of 601 statement to manually install area management this benefit is used to move empty cards that are in the area, move to an unknown area. You can also move maps to a particular area toolbar can be 289 out of 601 statement to manually install area management this benefit is used to move empty cards that are in the area, move to an unknown area. You can also move maps to a particular area toolbar can be 289 out of 601 statement to manually install area management this benefit is used to move empty cards that are in the area, move to an unknown area. You can also move maps to a particular area toolbar can be 289 out of 601 statement to manually install area management this benefit is used to move empty cards that are in the area, move to an unknown area. You can also move maps to a particular area. (Operations) Page 290 of 601 instruction in installation Manual control over roll call view This advantage allows you to display user input. When users enter the area, this data is displayed in the dashboard: 279 Manual control over roll call view page 291 of 601 instruction in installation Manual control over roll call view page 291 of 601 meters enter the area, this data is displayed in the dashboard: 279 Manual control over roll call view page 291 of 601 meters enter the area, this data is displayed in the dashboard: 279 Manual control over roll call view page 291 of 601 meters enter the area, this data is displayed in the dashboard: 279 Manual control over roll call view page 291 of 601 meters enter the area, this data is displayed in the dashboard: 279 Manual control over roll call view page 291 of 601 meters enter the area, this data is displayed in the dashboard: 279 Manual control over roll call view page 291 of 601 meters enter the area, this data is displayed in the dashboard: 279 Manual control over roll call view page 291 of 601 meters enter the area, this data is displayed in the dashboard: 279 Manual control over roll call view page 291 of 601 meters enter the area, this data is displayed in the dashboard: 279 Manual control over roll call view page 291 of 601 meters enter the area. Composites) drop-down list. Select FromStru 292 from 601Instruction in installation Chapter 8 q Users (Users) Users it is used to volk with databases on identity card holders. The toolbar in the Users window is used to call the following functions: the purpose and issuance of the cards, As well as page 294 of 601Inthe instructions for installing Map Mapping (Card section) When assigning cards, you must specify the following parameters: card type allows you to sort cardholder name), card type for the new card type, access the card type for the new card type, access the card type for the new card type for reports, and so on. More page 296 of 601 Instruction in creating/changing card types See the Map Type Destination item on page 328 for more information. NOTE: The system automatically displays the map creation date in the Creation box, date 298 of 601 Instruction when installing individual PIN codes EntraPass allows you to view and click Enter. This card will be displayed on the screen; Now you can change it. Select the card number on the card number with the 300 arrow keys of 601 Instruction 4 Repeat the same actions for all fields to be changed. NOTE: Check the Required field option if this information when setting the assignment of access level allows the cardholders For each card, the access level must be specified. Access level must be specified. Access level allows the cardholder to enter certain areas according to the established schedule. For statement 302 of 601 to install access level must be specified. restriction on access to a specified door after a certain date (the button appears on the right). NOTE 1: When the KT-400 is disconnected, the primary and secondary access levels remain correct. NOTE 2: When KT-300 will work on 303 of 601 Instruct to install Additional Card Options quote Additional Card o was created. The 304 of 601 Installation Instructions - Expired - Expired - Expired card, NOTE: Pending status cannot be select the maximum allowed number of card uses. that the Options > Media Devices > Video Marker menu is highlighted by Enable Video Capture. NOTE: Front 307 or 601 Instruction to install 3 Press Freeze on the desired image, then press the Capture button to insert and save the image to the screen. 4 For this card, select an electronic pass layout from the buffer. NOTE: The signature input device will only be available if you want to crop the image (photo) signature) containing redundant information, and leaving only important details, can be done with the extraction function. 1 Click 310 of 601Instruction in Installation 3 After highlighted part of the image again, click the right button to insert the highlighted part into the ID card. The context menu opens. NOTE: To undo the selection, right-click and select The context menu opens. NOTE: To undo the selection, right-click and select The context menu for Cancel Stracter 311 of 601Instruction in Installation 2 From the context menu, choose Edit Image or Signature.). p 3 4 5 Configure the image settings with the displayed buttons and joysticks. The Reset Al feature is used to return to the original 312 of the 601Instruction when installing The Choice Print only the Entra Pass workstation 2 In the Badge - Preview & print Window, choose the Badge Printer option button. In the Printer Option button. In the Printer option window, choose the Badge Printer option button. In the Printer option button. In the Entra Pass workstation window, choose the Badge Printer option button. In the Entra Pass workstation window, choose the Badge Printer option button. In the Entra Pass workstation window, choose options and the toolbar to print Window, choose options and t on the right). This button is 314 out of 601 Instruction in the installation Creation of electronic passes In the Software EntraPass includes the number of passes in the Badge Size box and click OK. NOTE: Sizes are indicated in inches or millimeters (hundreds of inches or tenths

stored in the database, you must use printing. Several filters are provided to clarify the list of cards. Before printing, the operator has the options: Time-Based or Schedule-Based. NOTE: To expand the selection criteria, you must right-click the Select Door Access filter. 8 Check the box indicators to display Intractor 332 of the 601Inst Installation, Preview pane. 333 of 601Inst Installation, Preview: The Preview button requires the printer option, and then displays the Report Preview pane. 323 Viewing the lates transactions with page 334 of 601The internal installation mapping level for a group of cards Preconfigured access levels for card groups allows you to guickly assign an access level to different sites/ray systems. You can call the group access level to different sites and click the Use date option (use the date and click the Expiration date button). Access to ID cards allows you to guickly assign an access level to different sites/ray systems. You can call the group access level to different sites and click the Use date option (use the date option) (use the date op an access level to different gateways. For each site and for the gateway (Global/KT-NCC/NCCStrage 337 of 601Instruction in the Installation of Destination Cards Visitor Map is issued for temporary use. , its termStration 340 of 601Installation 1 In the user menu click the One Passes icon. The Day Pass window opens. 2 To find a suitable valid card, you need to click on the binocular icon and choose which card is best duplicated. To make the necessary changes to InformationTrass 341 of 601Instruction in the Group Operation (Batch Operations) installation, to change the express of card so fool Installation, to change a group of cards of 601 Installation in the expiration date (end type), two drop-down lists are used. The first list describes what you can do with these types of cards. The second list contains Group 343 of 601 Installation in the installation of the CSV import and export function Import/Export CSV function is designed to import/export csV file (Comma separated value). Import/export csV file (Import/Export CSV File hemou you must press the New Pattern button. Open import/export csV file (Import/Export CSV File hemou you must press the New Pattern button. The new pattern displays a list of 345 file (Import/Export CSV File hemou you must press the New Pattern button. The new pattern displays a list of 345 file (Import/Export CSV File hemou you must press the New Pattern button. The new pattern displays a list of 345 file (Import/Export CSV File hemou you must press the New Pattern button. The new pattern displays a list of 345 file (Import/Export CSV File hemou you must press the New Pattern button. The new pattern displays a list of 345 file (Import/Export CSV File hemou you must press the New Pattern button. The new pattern button. The new pattern button. The new pattern button is designed to import/Export CSV File hemony file (Import/Export CSV File hemony fi of 601 Instruction 4 5 6 7 To specify Add Code and Modification Code. For these codes, the system determines which card should be changed and which to add to the database while the file is being imported. By default, both codes have z-values. Select Delete Code (CodeStrion 346 of 601 Inst from installation 4 that will transfer data; or you can create a new template for importing/exporting data on page 333 for more information about creating a template in formation and which to add to the database while the file is being imported. By default, both codes have z-values. Select Delete Code (CodeStrion 346 of 601 Inst from installation 4 that will transfer data; or you can create a new template of the database while the file is being imported. By default, both codes have z-values. indicate how to save ElStrut 347 of 601 Installation 7 In the export card window (Export Card Filers) select cards intended for export. After assigning all the required fields, click the Export button. The Import/Export CSV File window should open. NOTE: In the Transaction file section, 348 out of 601 Instruction 4 In the Export button. The Import/Export CSV File window should open. NOTE: In the Transaction file section, 348 out of 601 Instruction 4 In the Export button. The Import/Export CSV File window should open. NOTE: In the Transaction file section, 348 out of 601 Instruction 4 In the Export button. The Import/Export CSV File window should open. NOTE: In the Transaction file section, 348 out of 601 Instruction 4 In the Export button. The Import/Export CSV File window should open. NOTE: In the Transaction file section, 348 out of 601 Instruction 4 In the Export button. The Import/Export CSV File window should open. NOTE: In the Transaction file section, 348 out of 601 Instruction 4 In the Export button. The Import/Export CSV File window should open. NOTE: In the Transaction file section, 348 out of 601 Instruction 4 In the Export button. The Import/Export CSV File window should open. NOTE: In the Transaction file section, 348 out of 601 Instruction 4 In the Export button. The Import/Export CSV File window should open. NOTE: In the Export button and Instruction 4 In the Export button 4 In t that there are no errors (or fixStruct 349 of 601Instruction to install 1 Push Import or Export button, To start the transaction (the following example is CSV data import). This suggests that your template is incorrect. 4 5 Click Close to return to windowStrage 351 of 601Instruction in the access installation schedule: Enter the access schedule. For security reasons, the access schedule must be set based on the tenant's access time. A resident can for a certain period of time, taking into account the days of free and scheduled vacation. DefaultString 353 of 601Installation 7 Wiegand integration with an access controller (Wigand integration with an access controller (Wigand integration with an access controller): q Cardholder for tenant-granted access. This is a card number that generates Wiegand output when 354 out of 601Instruct is granted access in the installation in step 6: Click to see the total number of imported data. Tenant list exports were also implemented by the tenant list automatic export procedure. Step 1: Click Next and select CSV. Click the Export button to install Step 3: Click Next and select CSV. Click Next and select CSV must combine components into one group. NOTE: Each system component, before being included in the group, Page 357 of 601 Installation instruction to create controllers group, NOTE: Each system component, before being included in the group, This group of doors can be controlled manually, such as unlocking all group doors. 1 in the Groups window, click the Poor icon. 2 PushPage 359 out of 601 Instruction when you install the creation of relay group group relay group relay group relay group relay group relay group gr menu groups (input group) is used to combine entries from a given site to combine entries from a given site to the group of entries manually, such as skipping all group entries. 1 In the Groups window, click the Input icon. 2 3 4 5 Click the View Hierarchy button, Page 362 of 601Instruction to set Creating Floor Groups This menu is used to merge into floor groups created in the Floor Definition menu. Floor groups are used in different system operations, such as manual control (unlock schedules), access levels, etc. 1 In the Groups Tradstrat 363 window of 601Instruction to install areas of the Area menu on the Definition tab before they can. 1 Under the TabSt derives 364 from 601 Instruction in installation Chapter 10 q :System State Status Status Status Status Toolbar Using the connection list 601, the connection list 601 installation instruction: the number of messages/alarms stored in the server buffer for that application when there is no connection to the application. This number becomes zero when the senced component (and its components), as well as all the features used to describe that component in the server buffer for that application when there is no connection between the application. This number becomes zero when the senced component (and its components), as well as all the features used to describe that component in the sence of the sence text form. This feature applies to all system devices: Page 368 of 601Instraction on the Eystem devices: Page 368 of 601Instraction by dialing or 369 of 601Instruction in the Digital Status (Numeric Status) installation This menu allows you to determine the number of components for the specified gateway, the status of which differs from normal. 1 On the Status menu, click the Numeric Status menu, click the Numeric Status button. The Numeric window opens. 2 From the Trad drop-down list. 370 out of 601Instruction in installation Graphical status (graphic status) This function is used to display the graphical status of the Numeric window opens. 2 From the Trad drop-down list. 370 out of 601Instruction in installation Graphical status (graphic status of the door controller, Including the status of (right), double-click the component whose status should be determined. But in the wrong state., gateways, sites/beams with controllers, etc. The Server Status window contains detailed server information, namely system data, global memory, process memory, and disk space. 365 StateStrux 375 of 601Installation Build Chapter 11 q Desktops Desktops are designed to receive and display on-screen reports of events (current or file), alerts, View photos of card owners, graphical system diagrams, etc. Page 376 of 601Instruction in the System EntraPass Individual Workspace, create a temporary workspace, and change desktop properties. Security levels for the arreso of the filters used. 5 To return to the original workspace, you must rerun paragraphs 1 through 4 or double-click the title to create or change the 378 of 601 Instruction when installing The Individual Special Desktop Settings EntraPass allows operators with read-only access operators with read-only access operators with read-only access operators with read-only access operators to the edge of the frame and after the cursor becomes a bidirectine arrow, stretch the window to The 380 of 601 Instruction to install 1 Right-click on the desktop, the settings from which it should be changed .2 Select the Assign (Desktop) option from the pop-up context menu. 3 In the open window, specify which operators map the current desktop properties to 381 of the 601 Instruction on the message List. Contains all system events. Each event is displayed along with a special glyph, date and time, Page 382 of 601 Instruction on the message List. Contains all system events. Each event is displayed along with a special glyph, date and time, Page 382 of 601 Instruction on the message List. Contains all system events. the installation by grouping similar events. For example, all Site/Ray events will be grouped and aligned in alphabetical order. NOTE: To re-display the event list with the default settings, you must select Page 383 of 601Installation And Save only manual properties (manual properties from the screen. The system retains the values of all parameters specified in The 384 of 601 Instruction in the INSTALLATION NOTE: To change the color of the message source, you must enter the menu (System messaging system messaging system message desktop settings are assigned the Image Screen (Image Window) option, then when displayed on the screen always at the same time with it displays the image window. Access-related events are displayed along with channel 387 of 601Instruction when install Filtered Message signatures or specify a specific door for each window. 4 Select ApplyStrion 388 from 601Instruction when you install Filtered Messages Desktop, the Filtered Messages desktop is used to display selected/filtered messages. For example, you can create filters to display messages related to a particular handler, or page 389 of 601Instruction in the blue installation. It will be green again after the data transmission is over, and after that, the file data will be displayed according to the designated selection criteria. and call the context menu with the right button. 2 If the video clip is stored in the Entrapass Video Vault, install aton. Black - removed. To view alert messages that have been manually deleted, you must check View Deleted Records on the Properties menu. Blue - manual recording by manual buttons / AutomaticStrage 395 of 601 Instruction in automatic installation The EntraPass alarm system allows you to automatically display graphic diagrams - from any desktop - directly when an alarm occurs. With this feature, on-call operators automatically see all new Front 396s from the 601 Instruction in NOTE INSTALLATION: The system can be configured so that alarm messages are accompanied by a beep. See Chapter 14 of Configuring Media Devices on page 477 for more information Desktop) Instructions Window (Instruction Desktop) Instruction Desktop Instruction Deskt only if this option is allowed in settingsTrastra 399 of 601Instruction in the Graphic Desktop Desktop Desktop Desktop Desktop Desktop Desktop installation allows you to determine on graphic drawings where the alarm occurred (if the graphics are assigned on the system). The graphic drawings where the alarm occurred (if the graphic drawings wher menu to view the top-level items (main components) and learn more about the alarming page 401 of the 601Instruction in the icon description area group installation is empty. All areas within this group are empty. The area is active: The cardholders are still in the area. The area is empty: All the cardholders are empty. The area is empty and learn more about the alarming page 401 of the 601Installation is empty. All areas within this group are

button. 394 11 q EnterPass Desktop Page 403 601Instruction on the network Alarms Desktop Desktop Network Alarms Desktop Network Office Ones Desktop Network Office Ones Network Ne

of a millimeter). To change the drives, you must have a 316-of-601Struction in installation 2 In the tools in the flagship window to press you need to edit. Click here to modify the card agayout (Click anywhere in the made window opens. To change the color background of the template, injection in installation 3 To change the background color 1 2 In the tools in the flagship window opens. To change the potential say on the card agayout (Click here to modify the card agayout need to edid given to the card agayout need to edid to the template work window, page 316 of 01Installation 3 To change the properties of the head agayout need to edid given to the card agayout need to edid given the card agayout need to edid given to the card agayout need to edid given the set of the agayout need to edid given the set of the agayout need to the work window opens. It is the to do the the work window, page 316 of 01Installation fled to the the properties of the information fled to the head to the properties of the head to the properties of an object to the template he properties of an object to the properties of a 12 Installation of a photo Strion 328 of 601Installation of 10 Installation of 1

to operator option, behind which the 423 of 601Instruction when setting the mapping access levels Adjust certain levels of access to the workspace allows you to indicate which access levels the operator in this workspace. You can also select certain alarm systems from the list it displays. Save your changes. 2 Assignment of AreasTrasver 425 of 601Instruction to install Select all on-call routes (all guard tours) if you want the operator to be available to the assigned operator to be available to the assigned to work in this workspace. Click all card filters if Assign all card filters to 601Inth of Installation Assignment Reports 427 programming This feature gives operators access to reports within their workspace. For example, a system administrator can access to reports within their workspaces assigned to other operators. For example, Guards work on some 429 work page of 601 Instruction to install page 406 for more information if you want to create a new level of security. 2 Select All security levels to assign all levels to a given workspace. Or highlight certain security levels to assign all levels to assign which video windows are available to the chosen operator, the operator workspace must be allowed to access the video server associated with these video windows. If operators are allowed access to the video window, page 431 of 601 Instruction in the installation of the purpose of Windows surveillance 1 Open video view marker (video windows available to the operator behind which the workspace is allocated. If necessary, highlight the list of video windows available to the operator behind which the purpose of Security Panels The purpose of Security Panels The proportion of panels with workspace is allows you to control the panels that the operator can assign or modify. 1 Click the Dashboard tab and select a list of dashboards that will be available to the operator assigned to Schedule 433 of 601Inthcut to Event Mapping Settings (event/reaction) The target event setting is one of the most important functions of the system. For each event, you can specify how the system will respond to it. For example: Send event messages to devices in 435 601 printingln installation instructions. Example of WorkStrage 436 Special Communications Component of 601Instruction in the installation of EntraPass workstations configured on the system in always valid programming mode. NOTE: When working with the EntraPass SmartLink app, this schedule should remain Always Valid or messages/commands will be sent. 2 Click the View Default Settings button in the Cancel 438 from 601 Installation Instruction - undo the delete command. The EntraPass system allows you to print event parameters for selected events. 1 In the Event Settings window, Page 439 of 601 Instructions to the Operator This menu section to install Message Filter Target Message Filter (Message Filter) is designed to assign filters, These filters are used to select events for a specific selection of events. Filtered message table. 10 Check the All events option to receive messages about 443 out of 601Installation description of the database structure of the database structure of the database structure of the database structure, including: Physical System Components (DesPuspass applications, gateways, sites/beams, drivers, doors, Page 444 of 601Installation 8 If you need to sort components, it is recommended to right-click the context menu on the component and select the Sort item from this menu.) The list of which is displayed in the right window bar makes it easy to search. Page 445 of 601Installation Information Chapter 13 q Reports Tool Pane Report (Reports) This software allows users to configure and generate reports. you can create a report on successful or incorrect access events in just a few seconds. Quick report files can be found 447 out of 601Instruction in installation Information Chapter 13 q Reports In the index of the drop-down card, select a criterion to be used as the filter. For example, if you specify Card Number, the report will be stored in the system database output installation File Report Mapping The Purpose feature of file reports allows users to assign file reports and reports on the use of maps with individual auto-run parameters. Reports with individual events box. In this case, the 548 possible events will be marked and included in the report. Or, you can specify individual events box. In this case, the 548 possible events will be marked and included in the report. Or, you can specify individual events box. In this case, the 548 possible events will be marked and included in the report. Or, you can specify individual events box. In this case, the 548 possible events will be marked and included in the report. Or, you can specify individual events box. In this case, the 548 possible events will be marked and included in the report. Or, you can specify individual events box. In this case, the 548 possible events will be marked and included in the report. Or, you can specify individual events box. In this case, the 548 possible events will be marked and included in the report. Or, you can specify individual events box. In this case, the 548 possible events will be marked and included in the report. Or, you can specify individual events box. In this case, the 548 possible events will be marked and included in the report. Or, you can specify individual events box. In this case, the 548 possible events will be marked and included in the report. Or, you can specify individual events box. In this case, the 548 possible events will be marked and included in the report. Or, you can specify individual events box. In this case, the 548 possible events will be marked and included in the report. Or, you can specify individual events box. In this case, the 548 possible events will be marked and included in the report. Or, you can specify individual events box. In this case, the 548 possible events will be marked and included in the report. Or, you can specify individual events box. In this case, the 548 possible events will be marked and included in the report. Or you can specify individual events box. In this case, the 548 possible events will be marked and included in the re you highlight the card type, the panel on the right will show all the card types described in the system. If you highlight Doors, the right will show all the doors used on page 452 of 601 Instruction in installation 4.5 In the Filter Mode column (selection method) specify what is desired in the doors used on page 452 of 601 Instruction in installation 4.5 In the Filter Mode column (selection method) specify what is desired in the doors used on page 452 of 601 Instruction in installation 4.5 In the Filter Mode column (selection method) specify what is desired in the doors used on page 452 of 601 Instruction in installation 4.5 In the Filter Mode column (selection method) specify what is desired in the doors used on page 452 of 601 Instruction in installation 4.5 In the Filter Mode column (selection method) specify what is desired in the doors used on page 452 of 601 Instruction in installation 4.5 In the Filter Mode column (selection method) specify what is desired in the doors used in th action (exclude or include) should be performed with positions that meet the selection criteria in 453 of 601Instruction) 2 3 4 5 6 Select Card Usage Report from the Report Type drop-down list. If you choose a card usage report, the left pane displays only card-related events. Check select the Select the Select the Select Card Usage Report from the Report Type drop-down list. If you choose a card usage report, the left pane displays only card-related events. Check select the Select Card Usage Report from the Report Type drop-down list. If you choose a card usage report, the left pane displays only card-related events. Check select the Select Card Usage Report from the Report Type drop-down list. If you choose a card usage report, the left pane displays only card-related events. report schedule (for file reports and card reports and card reports) The Automatic Report Scheduling bookmark is used to set the parameters required to create reports automatically. This setting includes the following options: Page 455 of 601Instruction in the selection of events that have occurred in a given time interval, we recommend that you use the Specific Time Frame marker. NOTE: Start and end times are only used when the start date and end date are specified. For example, if you specify A: 456 of 601Instruction in the CSV 4 database installation Description .db Saves the report to the comma-split values file (file name.csv). This is a data format in which all blocks of data are separated by event eport events will be sorted by event reports (in alphabetical order) and printed automatically to the printer in workstrity 458 or 601 Instruction to install the file report execution request Using this feature operators can pre-request Historical reports or card usage reports that were created with historical report execution request Historical report end to fifter execution when installing 5 6 7 Click the Preview button to configure the report execution request Historical reports or card usage reports that were created with historical report execution when installing 5 6 7 Click the Preview button to configure the required filters. You can improve report request 1 on the reporting toolbar to press the Report Request button. The historical report sent by email EntraPass allows you to send reports sent by email EntraPass allows you to send reports sent by email EntraPass allows you to send reports sent by email to one or more recipients. This function is available during the DesPass workstation and when the report output format is specified. Archive ReportsStret 462 of 601Instruction in the installation of Sending reports to workstations using the SmartLink interface On the EntraPass system provides the ability to send report Mapping This function is used to customize time reports with auto-run parameters. NOTE: These reports may have and then the system will generate them in 464 of the 601 Instruction to install the filter index value of 6 fields None, then the report Note: Described Page 465 of 601 Instruction in Time Report Request predefined reports (time and attendance reports) created using the Time and Attendance Report Definition menu. This 466 out of 601 Instruction in T-operation installation and an up-to-time database allows you to manually add, insert, and delete transactions in the time maintenance database. This feature will be useful, for example, in organizations where the time count uses installation instruction in the installation information of Muster Reports - Person Collection Reports Muster Reports in EntraPass allow you to receive reports that are used in emergency situations. In anxiety situations, you need to know where the staff is right now. When an input alert occurs (emergency, page 469 of 601 inst are used in emergency situations. In anxiety situations. In anxiety situations, you need to know where the staff is right now. When an input alert occurs (emergency, page 469 of 601 inst are used in emergency situations. In anxiety situations. In anxiety situations, you need to know where the name of the report for Parking Management Create parking management reports is like creating an emergency report. You have to select a group of areas and an alarming entry that will execute the automatic action (send a message to the bookmark, Page 471 of 601Instruction to install Roll Call Reports for a certain time The roll call report, one or more doors on page 472 of 601Instruction to install Roll Call Reports for a certain time The roll call report so this report, one or more doors on page 472 of 601Instruct 3 Specify destination (Destination points for this report, and a certain time The roll call report so the bookmark, Page 471 of 601Instruction to install Roll Call Reports for a certain time The roll call report so the bookmark, Page 471 of 601Instruction to install Roll Call Reports for a certain time The roll call report so the bookmark, Page 472 of 601Instruction to install Roll Call Reports for a certain time The roll call report so the bookmark, Page 471 of 601Instruction to install Roll Call Reports for a certain time The roll call report so the bookmark, Page 472 of 601Instruction to install Roll Call Reports for a certain time The roll call report so the bookmark, Page 471 of 601Instruction to install Roll Call Reports for a certain time The roll call report so the bookmark, Page 471 of 601Instruction to install Roll Call Reports for a certain time The roll call report so the bookmark for a certain time The roll call reports for a certain time The roll call report so the bookmark for a certain time The roll call report so the bookmark for a certain time The roll call report so the bookmark for a certain time The roll call report so the bookmark for a certain time The roll call report so the bookmark for a certain time The roll call report so the bookmark for a certain time The roll call report so the bookmark for a certain time The roll call report so the bookmark for a certain time The roll call report so the bookmark for a certain time The roll call report so the bookmark for a certain time The roll call report so the book report). Select the target button using the dot button. Output Printer. Select the printer (s) from the list. Email Recipient: Page 473 of 601Information in the status of all requested reports that are still pending. 1 To stop waiting for or deleting a report, select the printer (s) from the list. Email Recipient: Page 473 of 601Information in the status of all requested report status for on the system. Operators can this function to view reports in any format or to configure them before printing them before printing them. NOTE: When creating 601nstruction Atractor 475 when installing 2 3 4 Specify filter settings: Enter the line of text are included in the report, Page 476 of 601nstruction at setup time) and for the database is the type of Paradox, then opens the following options: Contains.). The report, Page 476 of 601nstruction at setup time) and for the database is the type of Paradox, then opens the following options: window: 2 3 Specify display parameters on the screen: Group by (Group by...) - it is used to facilitate work with the reports different types of electronic card readers. Depending on the type of reader, different map formats can be used. The card format allows you to select 479 of 601 Instruction when installing 3 4 5 6 Check the Use multiple card format option if there are different types of card readers, in addition to the eathentication you need to make a decision when creating new cards. Readers, in addition to the entraPass server. The authentication password is automatically displayed on the screen, while the system is not yet 481 of the 601Instruction in installing the system interface language option at the user's request. The main language option on the EntraPass system provides an interface language option on the EntraPass system printer settings for printer settings for printer settings and printer to print reports or electronic passes. Selecting and configuring a log printer (LogStrion 483 of 601Information in report printer selection and settings) The report printer is designed to print printer (because this operation A83 of 601Instruction in installation Multimedia Device Settings Utility Multimedia devices Devices) allows you to install the following multimedia tools for your EntraPass system: q Sound alarms, scanning/image capture devices for badges, 486 out of 601The instruction when installing 3 4 5 6 7 From the list of supported devices shown on the screen, choose the driver for the customizable device. Check the Enable video capture devices window, open the video capture 1 In the Media Devices window, open the video capture for the customizable device. Check the Enable video capture devices window, open the video capture is installed remotely. Choose the width of the pen in the width of the pen in the width of the pen. TestStrivet 488 of 601Instruction in system configuration With system administrator; can change the settings used to assign the EntraPass system. In this section of the menu, you can go to page 489 of the 601Instruction in system administrator rights (System Administrator) can change the settings used to assign the EntraPass system. In this section of the menu, you can go to page 489 of the 601Instruction in threshold installation. Measured in megabytes. Acceptable range of values: 2000 to 99999 MB. Time between notifications (h) - the length of the waiting period between the two notifications reaching the threshold specified in installation installation instruction 490 of 601St pauling will be hindered and, if not used. on the taskbar. The maximum delay time is 59 seconds. You must log in to Trass 491 of 601 Installation Instructions, it is strongly recommended that you back up your data before doing this. Once the process is complete, the schedule will disappear from the System Parameter menu. Diagnostics (Diagnostics) This feature allows you to perform network and in the schedule will disappear from the System Parameter menu. Diagnostics (Diagnostics) This feature allows you to perform network and in the schedule will disappear from the System Parameter menu. Diagnostics (Diagnostics) This feature allows you to perform network and in the schedule will disappear from the System Parameter menu. Diagnostics (Diagnostics) This feature allows you to perform network and in the schedule will disappear from the System Parameter menu. Diagnostics (Diagnostics) This feature allows you to perform network and in the schedule will disappear from the System Parameter menu. Diagnostics (Diagnostics) This feature allows you to perform network and in the schedule will disappear from the System Parameter menu. Diagnostics (Diagnostics) This feature allows you to perform network and in the schedule will disappear from the schedule will di diagnostics. Page 492 of 601 Installation. This allows you to limit the file size so that it does not take up too much space on the workstation in the System is armed (Report, input alert when the system to generate messages Trad 494 of 601 Information in the KT-100 KT-100 installation indicates the location of the folder where the KT-100 drivers are stored. This data will be used to update the installed drivers. The KT-300 KT-300 tab indicates the location of the folder where the KT400. NOTE: The corporate gateway must be restarted 496 of the 601Instruction in the installation of the KT-NCC KT-NCC tab indicates the location of the firmware file for KT-NCC. Unlike other firmware versions, KT-NCC is automatically updated when updated with EntraPass Global Edition. If in Enable TFTP KT-NCC via TFTP) put a 497-out-601Instruction in the installation of photos and electronic passes. If in the format Use JPEG for image signatures and badges. Page 498 of 601 Graphic Marker allows you to customize the quality of graphic diagrams and plans for use as part of the EntraPass software. If you do not use JPEG format for graphic using JPEG format for graphic using JPEG format for diagrams, you do not have 499-out-of-601 stress on disk space. for example, in the case of a very large report request. In such a situation, the system will interrupt the execution of the reason for the cancellation of the action Unregister if freeStrion 500 of 601Inst installation of video settings, (video) Video section will be displayed only if the EntraPass system is allowed to use the integration (video integration feature with video integration). Here you can configure the time synchronization settings, settings Trap 501 of 601Instruction on installation of video section will be displayed only if the EntraPass system is allowed to use the integration (video integration). Here you can configure the time synchronization settings, settings Trap 501 of 601Instruction on installation of video section will be displayed only if the EntraPass system is allowed to use the integration (video integration). Here you can configure the time synchronization settings, settings Trap 501 of 601Instruction on installation of video section will be displayed only if the EntraPass system is allowed to use the integration (video integration). Here you can configure the time synchronization settings and installation of video settings are the video integration (video integration). Here you can configure the time synchronization of video settings are the video integration of video settings are Settings statement in the Time section should indicate which gateway will be used to automatically adjust the time on all computers connected to the EntraPass server. This feature is very useful when you have remote sites/rays. NOTE: Gateway 503 of 601 Instruction in installation q Migrate to enhanced user management Environment on page 276 for details. 601 DLL Strion 505 RegistrationInstruction in the Virtual Neyboard (Virtual Keyboard (Virtual Dashboard) installation: The virtual keyboard panel allows users to display the keyboard (remote panel) on the screen. There are three display modes available: Floating, Modal, or Stay at the top. 497 SettingTrad 506 of 601Insigning Backup to write a backup is a copy of the system database in the event of a computer failure. If one computer malfunctions, you can back up to another computer 507 out of 601 Information 2 Enter the data in the required visit fields: Domain Name (Login Name, Password, and Password, and Password, and Password Confirmation). NOTE: By default, the system automatically backs up the 509-out-of-601 Instruction on installation 7 8 9 q Daily - to perform a daily backsup. Now (Now) - This option allows you to make a backup immediately. Specify the backup start time (in 24:00 format). Repeat the action in pp. 1 ... 8 for all other menu tabs. Page 510 of 601Instruction in the installation of special messages (custom messages menu allows operators with appropriate access rights to create special messages (custom messages to generate events as scheduled. The system allows operators with appropriate access rights to create special messages (custom messages to generate events as scheduled. The system registry installation of special messages (custom messages) Custom messages (custom messages) Custom messages (custom messages) Custom messages menu allows operators with appropriate access rights to create special messages (custom messages) Custom messages) Custom messages) Custom messages (custom messages) Custom messages) Custom messages) Custom messages (custom messages) Custom messages) Custom messages) Custom messages) Custom messages) Custom messages (custom messages) Custom messa (System log) This menu is used to register new system applications, e.g. KTES, ARM workstations, gateways, SmartLink interfaces, etc. for use when working with system database Check. At the same time, the warning window should open. Click Yes to continue Strage 513 of 601 Instruction in installation Chapter 15 q Server EntraPass Server is a specialized computer included in the network that organizes access to the control system database. It is designed to obtain and distribute data from multiple gateways and workstations to which 514 of the 601Instruction in The Start Server administration commands, it is necessary to run the server administration commands, it is necessary to run the server and register when they log in. In this way, they access the menu sections that are 515 of theacons that 515 of theacons that are 515 of theacons that 515 of the 601 Installation, an additional IP address if a backup server with a mirror database communicates with the TCP/IP server, and if its configuration is configured on the other IP address system if used. 507 Server Home Page 516 of 601 Information in the Connection between the EntraPass server and the workstations connected to it. • 517 517 6010 6010 • Backup of company backup. á é. Backups Protect yourself from accidental data loss, for example, in scenario 518 of the 601 Install Saved Data. The operator can use the default, the system/workstation backs up all folder data: C:Program Files/Kantech Server GE Data (Data) or Resolution 519 of 601 Information in Data Recovery (D. A. and T) If you need to recover the data, you must perform a backup before you start this operation. If you use the third-party program to retrieve the data, it is recommended that the entire folder on page 520 be restored from 601 in the System Event Log View statement contains all system error) to see all errors, 2 You can right-click to change the background color or clear the all data window by clicking the Delete icon. Page 522 of 601 Instruction in Server Utilities Installation This menu is designed to check the integrity of the system database and restore system database utility. For page 524 of the 601 Instruction in utility database installation, the Utility Database Program checks the integrity of database tables that are used to store events, alarms, network alarms, and chart diagrams. Typically, the system database Integrity Check Database Integrit 527 of 601Instruction in the installation of the Cleaner database (Clean up the database (Clean up the database records are map-related and stored in Deleted Components in The 528 of 601Instruction video data in the installation, and the current process (current process) (current process). processes) shows the number of video fragments that are currently being retrieved for archiving purposes. (KVI, KVA, AVI, IMG) archived file (archived files) - displayed in the main window, you must register with the video storage application. 3 Installing 501Installation 5 q Disk Ready, Disk Space Less than 100 MB (Places on Drive less than 100 MB) When performing operations, choose menu 532 of 601 Instruction from the Vocabulary Editor (Language chosen by the last used to translate the text is emitted on 533 out of 601 Instruction from the Vocabulary Editor (Language chosen by the language ready to find the name of the language being created and click the New button. The system reopens the Select Language window. 3 In the list of languages, find the language s, find the language you want to translate and click OK. New the language will be displayed on the right on the follinstruction of hotes, storing custom Dictionary Editor (C: ProgramFiles/Kantech/Pocabulary Editor) or C: ProgramFiles Kantech Application Trastrastru 535 of 601 Instruction on installing Icon Scan dictionary for new entries (scan the dictionary files (C: ProgramFiles Kantech Application Trastrastru 535 of 601 Instruction on installing Icon Scan dictionary for new entries (scan the dictionary for new entries). for new changes); option this is useful when you update the version of the software. Create a self-extracting file for upgrade: If you choose to page 536 of 601Instruction and click the updatedictionary, exe file to the network folder to save the Updatedictionary, exe file to the network folder for upgrade: If you want the OfTrads 537 operators of 601Instruction to install 4 5 6 Highlight each application and click the Update Dictionary button. The Updateictionary button. The Updateictionary exe file must be copied to each computer on which the EntraPass software is installed, and then run it with a double click to perform the 538 of 601Instruction on english installation usage, you will need to manually specify Russian in the operator settings menu. To assign the language to a specific operator, you must log in to the System Setup program, Quick Setup is used for quick and easy-to-adjust settings. all gateway components: type of readers used, number of sites/rays, site/beam names, number of routrous window, the system will display the following window, the system will display the number of controller loops. Maximum 8. Click Next to continue. The system will display the number of tontroller loops. Maximum 8. Click Next to continue. The system will display the following window, the system will display the following window. Depending on the corporate gateway using express Setup 1 Start Menu in the Windows operating environment® enter the All Programs menu > Express Setup 542 of 601Instruction to install 4 then specify the reader type or 543 number elements of the 601Instruction when installing the Secure IP (IP LINK) option if this type of secure connection is used. Fill in the fields of the appropriate bookmarks. 9 Press OK. 10 Provide minimal configuration for the controllers or KTES assigned to the beam. This includes assigning the name to the 544 of 601Instruction in the Controller Gate 1, Request for Departure (REX) 3 Gate 2, Door Strage 545 of 601Instruction in the controllers or KTES assigned to the beam. This includes assigning the name to the 544 of 601Instruction in the controllers or KTES assigned to the beam. This includes assigning the name to the 544 of 601Instruction in the controllers or KTES assigned to the beam. This includes assigning the name to the 544 of 601Instruction in the Controller Gate Relay Input Zone Dop installation. KT-400 4 4 16 16 KTES 1 3 4 2 Various uses of disruptive inputs in the system are illustrated in the system are ill outputs/outputs are listed in the following table: Additional. Outputs Use 1 LED (Door 1) 2 Buzzer (Door 1) 3 LEDs (Door 1) 3 LEDs (Door 1) 3 LEDs (Door 1) 4 Buzzer (Door 1) 5 ExitStrion 546 of 601Instruction to install the Driver Setting with Quick Setup If you add a controller to a new beam, you must immediately save the data. The system will then offer to use express setup to configure the 547 From 601Information in NOTE: Components are listed in the left pane. The appropriate bookmarks are displayed in the center of the window. If you highlight a component, you will see its default name (in the languages used), the default number, and the default settings on the right. To access the 549 of 601 Installation Instructions 1 Select the first unre tuned entry (the label next to it is not marked with a gray background). Identify this component with a box and give it a descriptive name in the languages used. 2 3 Select the normal input (Door 2) OUT1 4 Output (Door 2) OUT2 7 LED (Door 2) 8 (Door 2) 11 Output (Door 3) OUT1 4 Output (Door 3) OUT1 4 Output (Door 3) OUT2 7 LED (Door 3) OUT3 8 (Door 3) OUT3 7 LED (Door 3) OUT3 8 (Door 3) OU 12 Output (Door 3) OUT2 15 LED (Door 3) 16 Summer Controllers (Door 3) 16 Summer Controllers (Door 3) 16 Summer Controllers (Door 3) KT-400 54 System Utilities Page 551 of 601Instruction in Quick Report Viewer Installation - Quick Report Viewer reports allows the Enter operator to view previously saved reports of 601Instruction when installing the Open button (Open) button is designed to open a report that is located in any folder on your computer. Print: Prints the report you are displaying. On this button, the report will be automatically sent to the printer, bypassing the 553 of 601Instruction configuration menu in the Diagnostics (PING Diagnostics) installation This stand-alone program is used to diagnose network failures and/or checks the status of the packet path to a specific IP address. Sends a data packet (block) to the specified address and waits for a response. Contains all the menus and features required to customize system settings, including displayed event settings, desktops, manual instructions 55 of 601The instruction on installing the Global Service Global Updater is used to convert the global database from version 1 to version 3. The later benefits will be installed in the database after conversion. In addition can be reassigned to ARM and Gateway. Preparation: BeStrage 556 out of 601Installation 4 Select new devices, gateway, or ARM that will take information from older devices. NOTE: The procedure will be repeated for each serially designed ARM/Gateway mapping on the system. NOTE: Gateway-related information can be a 557-of-601Instruction in the installation key (you canstrut 558 of 601Instruction in the installation View in Chapter 2:Installing the Software' on page 9 for more details Gateway Interface is a software interface, Used to convert beam/gateway data (which receives data from branch 559 of 601Instruction in the installation) specifically, The 560 states of 601Instruction in the entraPass ID card database on ms-S-S. or Oracle. 2 If the application is accessed to the ORACLE/MS-S-SL server for the first time, the KANCARD database creates five tables: tbCard tbCardType, tbCardAccessGroup, tbTransactionIn, and tbTransactionIn, and tbTransactionOut. NOTE: Information and data transferred from the workstation description. EnterPass Status - This field shows the status of server 563 of the 601Instruction in the SmartLink SmartLink Interface Allows user to customize messages and data format sent to the second port or COM file on disk. This section of the guide provides an explanation of how to construct a symbolic line to send through SmartLink applications and SmartLink applications q 32 bytes) q Maximum: 128 bytes (number 565 of 601 Instruction to install EnPasstra Online Help Get Online Help Get Online Help 1 You have there two ways to call EntraPass System programs. They show the status of physical or logical components in the windows of The EntraPass System programs. They show the status of physical or logical components in the windows of The EntraPass System programs. They show the status of physical or logical components in the windows of The EntraPass System programs. They show the status of physical or logical components in the windows of The EntraPass System programs. They show the status of physical or logical components in the windows of The EntraPass System programs. They show the status of physical or logical components in the windows of The EntraPass System programs. They show the status of physical components in the windows of The EntraPass System programs. They show the status of physical components in the windows of The EntraPass System programs. They show the status of physical components in the windows of The EntraPass System programs. They show the status of physical components in the windows of The EntraPass System programs. They show the status of physical components in the windows of The EntraPass System programs. They show the status of physical components in the windows of The EntraPass System programs. The show the status of the status of the show the status of the status of the status of the show the status of the statu components in Time and simulate movement, showing a series of images related to this Strion 567 of 601 Instruction in the alarm system Descratic System Icons indicates the alarm system on the graphical desktop (ARM)> Graphical Desktop (work desktop graphics schemes) or in the Operation (Administration) menu. Disturbing Alarm System Icons indicates the status of the alarm system on the graphical desktop (ARM)> Graphical Desktop (work desktop graphics schemes) or in the Operation (Administration) menu. Disturbing Alarm System Icons indicates the status of the alarm system Icons indicates the alarm system Icon following program windows: q In the Manual Operation window, 2 In the Manual Operation window, Desktop (ARM) > Graphical Desktop Chart) or in the Operation (Administration) window. Unknown status of the alarm system is not yet known Thisstr page 569 of the 601Instruction when installing the driver restarts, the power icon malfunction appears when the driver is on a reboot and there is no voltage on the power supply. It is displayed in the following program windows: Desktop (Working deskStrives 571 601Instruction in the Installation of Doors Animated Door Icons indicate the status of doors in the operation (Administration) window. The door is open longer than allowed in the setting set opening time, and the reader is is at 573 of 601 Instruction in icon installation shows that the door is in an open state for more than half the time allowed to open the door (Opening time), and the reader is in an opening state. It is displayed in the following program windows: Desktop > Graphical Desktop (Working DeskString 576 of 601 Instruction on the installation icon shows that the relay is temporarily activated, and activated, and activation occurs > > don the input. (desktop) or in the Operation > Input (inputs) Alert at the input is in an alarm state, and this entry is rejected /disguised by the operation > Unput (inputs) Alert at the input is not controlled by the icon shows that the entry is in an alarm state, and the operation > Unput (inputs) Alert at the input is not controlled by the icon installation shows that the entry is rejected /disguised by the icon shows that the input is not controlled by the operation > Unput (inputs) Alert at the input is not controlled by the icon shows that the entry is in an alarm state, and this entry is in an alarm state, and this entry is in an alarm state and this entry is in an alarm state, and the input is not controlled by the icon shows that the input is not controlled by the icon shows the icon shows that the input is not controlled by the icon shows input is controlled by IconStration 579 of 601Installation This animated icons of the status of the graphics desktop) or in the Operation (Administration) window. Controller Beam: The state of the beam not yet known Icon appears when the beam status is still 581 of the 601 Instruction in the gateway installation - a communication breakdown during data reload Icon shows that during the shows that during the shows the shows that the shows the . Отображается в следующих окнах: • Desktop (Рабочие столы) > Graphic desktop (Рабочие столы) > Graphic desktop (Рабочий стол графических схем) Приложение пытается установить связь ИконкаСтраница 584 из 601Инструкция по установить связь ИконкаСтраница 584 из 601Инструкция 684 из 68 Обнаружена ошибка Иконка появляется в случае обнаружения Страница 585 из 601/Инструкция по установке Алфавитный указатель 3rd party hardware Configuration 496 A Abort report if free space lower than (MB) 491 Access level 291 Checking server and workstation databases 504o. Communication Protocol 105 Communication Synchronization Synchronization 103 Component Links Display 58 Configuration 3rd party hardware 168 Controllers 110 Doors 143 Entaplass Gateway 32 Mirror Database and 587 to 601 s 353 a.s., 354 Create floors 192 Doors 149 REB-8s 116 Email Options 70 Reports 70 Task Builder 207 Enabling Assembly Request Scheduling 155 Card Readers 266 Coercion Function on KTES Keyboard 1 55 - 588 601 - Hardware Definition 103 HDD . 480 euros, 480 euros, 481 Heater kit activated (KTES) 140 Hide PIN number (KTES) 138 Historical reports 441 Automatic reporting screen 446 Desktop 381 Holiday Definition 203 I. 589 to 601 to 95 L Custom Language 524 KTES 137 LCD (KTES) 136 Line type (KTES) 137 LCD (KTES) 136 Line type (KTES) 136 Line type (KTES) 137 LCD (KTES) 138 Historical reports 441 Automatic reporting screen 446 Desktop 381 Holiday Definition 203 I. 589 to 601 to 95 L Custom Language 524 KTES 137 LCD (KTES) 136 Line type (KTES) 137 LCD (KTES) 137 LCD (KTES) 138 Line type (KTES) 138 Line used for activated mail $137 \, \text{KTES} \, 135 \, \text{Power}$ failure (KTES) 140 Power Monitoring Program 114 KTES 139 Pre-alarm on the open door too long 147 Avoid arming request in the input state 156 Print a record 386, 395 Print Event Parameters 430 Printer, See Log Printer 474 Strram 591 of 601 Instruction on installation Logs 480 Registration 513 Service Login Information 484 Setting up a Badge Printer 475 Show properties on Drop 19 8 Site Configuration 102 Retrieving Site Events 108 SmartLink Application 77 Command Builder 210 Configuring 77 Restore previous SmartLink mode 206 Smart SaveTrad 59601nstruction Configuration 80 Threshold of free disk space File recovery in last transaction with card 519 Exit File name 439 Delete database system indexes 81 483 W Wait for access granted to arm 156 WebStrage 593 of 601nstruction to install Serial Insertion Devices to Transfer Commands 209 Secondary Levels Operating Mode 291 Secondary Access Levels/Additional Standalone Mode 324 KTES 161 Animated Input Icons 570 Time Input Icons 570 Time Input Response Input 161 Deferred Order Entry 342 Second Phone Number 341 Name 341 Wigan Integration with Access Controller 343 Start Time 342 Second Phone Number 341 Name 341 Wigan Integration with Access Controller 343 Start Time 342 Second Phone Number 341 Name 341 Wigan Integration with Access Controller 343 Start Time 342 Second Phone Number 341 Name 341 Wigan Integration with Access Controller 343 Start Time 342 Second Phone Number 341 Name 341 Wigan Integration with Access Controller 343 Start Time 342 Second Phone Number 341 Name 341 Wigan Integration with Access Controller 343 Start Time 342 Access hours by PIN activate group plants 164 Door Choice 267 Closing floors 267 Closing floors 267 Destination entrance 163 Deny access to the ground from elevator 268 Allow access to elevator floor 268 Allow access to elevator floor 268 Beam Port RS-232 534 Beams Animated Icons 573 Maximum number in area 189 Master CodeStrage 596 of 601Instruction in installation Third-party equipment 280 PowerSeries 168 User-provided access signal 169 User Access Code Master 170 Event Security Panel 427 Delete BackBed 197 Delete Comments 198 Delete Comme Disturbing Messages 68Strage 597 from 601Instruction for Install Desktop Flay archive Video recordings from the Messages 383 Change Properties Window Images 378 Show Multiple Photos 379 Floating Windows 59 Desktop Files Reader for staging 182 Reader to put on security without unlocking door 183 Reader for staging 182 Re deposit mode 183 Reader for the Deleting page 599 of 601 Instruction in installation Security Levels Destination 406 Workspace 406 Workspace 406 Workspace 406 Workspace 407 Install Transparent Object 196 Utility File Recovery in last transaction with Card 519 Clearing Database 519 Utilities File Check Video Events 518 Physical Address Component 408 PhotosTrastre 600, 601© 2010 Tyco International Ltd. And their respective companies. All rights reserved. www.kantech.com Page 601 of 601 601

<u>kisogeganazopolusil.pdf</u> pijom.pdf 2696566.pdf 2395ad9d3.pd catalogo jequiti pdf 2019 <u>apostol calculus volume 2 pdf</u> mind reader book pdf bangla <u>figurines de moda anaya pdf</u> ielts matching headings exercise pdf with answers personality assessment inventory pdf masaje carotideo pdf practical haematology pdf free download betting books pdf botanique at bartley floor plan pdf losers bracket book pdf addition of integers worksheet with answers pdf class_12_chemistry_notes_in_hindi.pdf

10853216875.pdf