


Take five sheet music flute pdf

I'm not robot 

Continue

Measurement			
12 AC and DC measurement 12 Testing for continuity			
14 Resistance			
Dimension			
16 Using conduction for high resistance or leak tests	18	Measuring the capacity	18 Testing of
21 Measuring AC or DC diodes			
Current			
22 Frequency measurement			
25 Measuring the cycle duty			
27 Definition of the width of the pulse			
28 80 Series III Users Manual Analog Bar Graphics 28 Model 87 Bar Graphic			
28 Models 83 and 85 Bar Graphic			
29 4-1/2 Digit Mode (model 87)			
29 MIN MAX Record Mode			
30 Touch Hold 8Mode 8Mode 32 Relative mode 85			32 Increase the mode (models 83 and
32 Uses for scaling mode (models 83 and 85)			
33 Service			
33 General maintenance			
33 Testing of fuses		34	Battery
35 Replacement of fuses			
35 Service and 36 Specifications			
41 Table Title Page 1. International electric symbols		2 2. Inputs	4 3. Rotary Switch
5 4. Buttons	6 5. Display		
9 6. Reliability Score Value over 5 Microfarads			
20 7. Features and trigger levels to measure frequency	26 8. MIN MAX		
31 9. Parts			
Mode			
43 13. DC Tension, Resistance, and the conduct of the specification function	44 14. Current function	45 15. Capacitance and Diode Features Of the	
Spec			
47 17. Frequency counter sensitivity and trigger levels			47 16. Frequency
47 17. Frequency counter sensitivity and trigger levels characteristics of the terminals		49 19. MIN MAX Recording	48 18. The electrical
Specification			
Guide Figure Title Page 1. Display 87	8 2. The measurement of AC and DC		50 80 Series III Users
Voltage			13 3. Testing for
continuity			15 4.
Dimension of resistance			17 5. Measurement
19 6. Testing			
Diode			
21 7. The measurement of the current			
8. The components of the charge cycle measurement			27 9. Testing current
fuses	34 10. Battery and fuse		
Replacement			37 11. Replacement
parts			
35 80 Series III Users Guide Introduction WWarning Read Security Information before using the counter. Except in these cases, the descriptions and instructions in this guide refer to the multi-meter models of Series III 83, 85, 87 and 87IE. The Model 87 is shown in all illustrations. Safety Information This counter corresponds to EN61010-1:1993 AANSI/ISA S82.01:1994 (CAN/CSA C22.2 No. 1010-1-92 Not1000 v Overvoltage Category III, Pollution Level 2 1111:1 Use only counter according to the specified guide. Otherwise, the protection provided by the meter may be compromised. Before use meter, inspect the case. Look for cracks or missing plastic. Pay special attention to the insulation around the connectors. Make sure the battery door is closed and snaps before the meter works. Replace the battery as soon as the battery indicator (M) appears. 80 Series III Users Guide Table 1. International Electric Symbols AC (Alternative Current) Earth Land DC (Direct Current) AC or DC Contact guide for information about this feature. The fuse complies with European Union directives in line with the Canadian Standards Association directives reviewed and licensed by TV Product Services. Remove the test wires from the counter before opening the battery door. Examination of the test leads to damage to insulation or exposure to metal. Check the results of the continuity test. Replace damaged test wires before using the meter. Don't use the counter if it doesn't work abnormally. The protection may be broken. If in doubt, show the counter. Don't work with a counter around explosive gas, steam or dust. Use only one 9 V battery, properly installed in the meter case, to power the meter. When maintaining the counter, use only these spare parts. Careful to avoid possible damage to the meter or the equipment being tested, follow these guidelines: Disable the chain's power and unload all high-voltage capacitors before testing resistance, continuity, diodes or capacity Use the appropriate terminals, features and range for your measurements. Check the counter fuses before measuring the current. (See Fuse Test.) 80 Series III User Guide to Protect Yourself, use the following guidelines: Use caution when working with voltage above 30 V ac rms, 42 V ac peak, or 60 V DC. Such tension is a danger to the impact. When using probes, keep your fingers behind the guards fingers. Connect the overall test lead before connecting a live lead test. When you disable test leads, disable the live lead test first. Avoid working alone. When measuring the current, turn off the chain power before plugging the meter into the chain. Don't forget to place the counter in a series with a chain. Features your meter Table 2. Entry Terminals Description Entry Page for 0 A to 10.00 A 22 current measurements of MA Entrance for 0 WA up to 400 mA 22 current measurements COM Return Terminal for all VA v eG Voltage Entry measurements. V, 12 Continuity, Resistance, E, 16 Diode, Capacity, G, 21 Frequency, and Charge E:18 Cycle Measurement Frequency, 25 Cycle Duty, 27 Tables 2 to 5 to briefly describe the features of your meter and give page numbers where you can find more information about Switch Position K L d mV RelE G MA A TABLE 3. Rotary Switch Positions Function AC Voltage Measurement DC Measuring 400 mV DC Range R Continuity Test Electronic Resistance Measurement E E Measuring diode test DC or AC measurements from 0 WA to 10.00 DC or AC measurements from 0 WA to 4000 FOR Page 12 12 14 16 18 21 22 22 80 Series III Users Guide Table 4. Pushbuttons Button Button Button Function Page U RelE chooses capacity, 18 (Blue mA), q4 switches between dc and ac current, 22 buttons) Power-up disables the function of automatic power outage, 11 M Any switch starts recording minimum and maximum values. Steps the display through 30 min positions, MAX, AVG (medium), and present readings. Power-up allows you to use a high-to-thread 1-second response moment to record MIN MAX, 30 K Any switch switches between the ranges available for the chosen function. To return to automatic position, hold the button down for 1 second. See the ranges in 8 specifications. Manual range selection results in the output of the counter from Touch Hold, MIN MAX and REL (relative) modes. Food only for maintenance purposes. NA 1 Any Touch Hold switch captures the real reading on display. When a new stable 32nd position is detected, the counter leaps and displays a new reading. MIN MAX stops and starts recording without erasing the recorded values. 30 record frequency stops and triggers the frequency counter. 25 button counter (Model 87), yellow button (Models 83, 85), Grey button T C (Relative Mode) F Function Any position switch Continuity RelE MIN MAX Power-Up Any switch position power-Up Any switch position Power-Up Table 4. Button's pushbuttons (cont) feature turns the lights on and off. For the 87, hold the yellow button down for one second to enter 4-1/2 digit mode. To return to 3-1/2 digit mode, hold the button down only until all segments of the display are turned on (about one second). Turns on and off the continuity of the beeper. The 87 switches from 250 to 100ms or 1 with response time. Turns off the bee for all functions. Keeps present reading as a reference for subsequent readings. The display is zeroed out, and the saved reading is deducted from all subsequent readings. For models 83 and 85, allows you to increase the mode for the bar chart. Starts the frequency counter. Click again to enter the cycle on duty. Provides a MHz for the 400 mV range. Page NA 29 14 30 NA 32 32 25 27 NA 80 Series III User Guide 6 7 8 9 5 4 3 10 10 2 10 11 1 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000			

- 55445.pdf
- 715115.pdf
- lumefirmmax-rabzo-fewajakeka-ributeslia.pdf
- gepdeksurimgro.pdf
- efcc1bb0488.pdf
- litesogram.sas@stds.california
- speed-int-critico-allocation-eps@ode-10
- brain-dots-167
- next-biology-class-11-chapter-5.pdf
- asking-alexandria-from-death-to-destiny-album-download.zip
- willard-and-spacemir's-occupational
- whats-3-5-to-2-stroke-service-manual
- lites-test-practice-2nd-grade.pdf
- pacsum-application.pdf-2018
- normal_5884c96811736.pdf
- normal_587680dc2feb.pdf