




I'm not robot



Continue

Here you will find a step-by-step video explaining how to change and or access the Summer Escapes pump inside our ground filtration system. (Click on the link below) Before assembling the product, you should take a few minutes to check the contents and familiarize yourself with all the parts. ⚠️WARNING - DO NOT overfill the pool and/or let people lie down or sit on the pool wall – THIS WAY CAN CAUSE PERMANENT DAMAGE! Drain the pool to the right level after heavy rain. TIP: It will be much easier to install the pool if you develop it and allow it to lie in direct sunlight for about 2 hours before installation. This will help ensure a wrinkle-free fit, as the pool material will become more pliable, allowing it to form into shape during installation. ⚠️Warning - VERY IMPORTANT! THE TERRAIN MUST BE HORIZONTAL, STABLE, COMPACTED SOIL. The pool must be assembled on a smooth and even place of hard soil, which is free of stones, gravel, sticks, blacktop or other oil base compounds. Do not install the pool on a wooden deck or on any wooden surface. You cannot use sand and/or soil without being emased to provide an even area for this pool; will only wash off. FAILURE TO FOLLOW THE INSTRUCTIONS BELOW WILL CAUSE THE POOL TO COLLAPSE AND VOID THE WARRANTY! 1. Select the level area and completely remove all impurities, twigs, stones, etc. DO NOT select an area under overhead electrical lines, trees or within 15 feet of your home, building, etc. The swimming pool is located at a minimum distance of 1.83 m from any electrical outlet. 3. All 125 V, 15 and 20 A sockets located at a distance of 6.0 m (20 ft) from the pool must be secured by a ground failure circuit breaker (GFCI). The distance of 20ft (6m) is measured by the shortest straight line distance a power cord would follow without piercing the floor, wall, ceiling, door, window or other permanent barrier. 4. Contact your local media to see if there are any underground cables, telephone lines, gas lines, etc. under the selected area. 1. Find a flat, horizontal area to set up the pool. Make sure the ground is free of sharp objects that can pierce the pool. 2. Carefully unfold the pool and check the seams for manufacturing defects. Lay the pool flat on the ground. Let the pool sit in the sun for at least two hours before installation. This will help ensure a wrinkle-free fit, as the pool material will be more pliable, so it will shape during installation. 3. Locate the pool so that the pump is 10 to 21 feet away from the power outlet. 4. Install the filter/pump system and connect the return connector using the and the suceling coupler with the suiling cap. Make sure that the drain cap is properly installed and that the cap is in place. 5. Fill the pool with about an inch of water. Pause to smooth out wrinkles at the bottom of the work pool from the inside out. Make sure that the floor is round in the apartment, and then pull out the outer wall from under the upper ring around the bottom of the pool so that it fills evenly. 6. Continue filling the pool, the inflated ring will increase as the water dredging. The maximum water level is located at the bottom of the inflatable ring. **All capacities and time frames are approximate** Pool size, pool capacity in gallons 80% 330 series 350 Series 400 Series 600 Series 700/800 Series 1000 or 150 10 Series Sand Filter 1500 Series 1500 Sand Filter CP2000-C 2000 Series 5'x15 106 8'x26 548 1.7 hours. 1.6 hours 1.4 hours. 8'x30 608 1.8 hours 1.8 hours 1.6 hours 1.0 hours 9'x26 708 2.1 hours 2.1 hrs 1.8 hours 1.2 hours 1.0 hours 9'x30 835 2.5 hours 2.4 hours. 2.1 hours 1.4 hours. 1.1 hours 10'x30 1,052 3.2 hours 3.0 hours 2.7 hours 1.8 hours 1.4 hours. 1.1 hours 12'x30 1,441 4.4 hours 4.2 hours. 3.6 hours 2.4 hours. 1.9 hours 1.5 hours. 12'x33 1600 4.0 hrs 2.7 hours 2.1 hours 1.6 hours 12'x36 1815 4.6 hours 3.1 hours 2.4 hours. 1.9 hours 12'x39 1,950 3.3 hours 2.5 hours. 2 hrs. 13'x33 1888 3.2 hours 2.5 hours. 1.9 hours 13'x39 2070 3.5 hours 2.7 hours 2.1 hours 1.5 hours. 14'x36 2300 3.9 hours 3.0 h 2.3 hours 1.6 hours 1.6 hours 14'x42 2547 4.3 hours 3.3 hours 2.6 hours 1.8 hours 1.7 hours 1.6 hours 15'x30 2270 3.8 hours 3.0 hours 2.3 hours 1.6 hours 1.6 hours 1.4 hours. 1.2 hours 15'x36 2640 4.4 hours 3.4 hours. 2.7 hours 1.9 hours 1.8 hours 1.7 hours 1.4 hours. 15'x42 3240 4.2 hours 4.6 hours 2.3 hours 3.0 hours 2.0 hours 1.7 hours 2.3 hours 15'x48 3700 4.8 hours 3.7 hours 2.6 hours 2.5 hours. 2.3 hours 1.9 hours 1.9 hours 16'x42 3600 4.7 hours 3.6 hours 2.6 hours 2.4 hours. 2.3 hours 1.8 hours 1.8 hours 16'x48 4,038 5.2 hours 4.1 hours 2.9 hours 2.7 hours 2.5 hours. 2.1 hours 2.1 hours 18'x42 4,718 4.8 hours 3.4 hours. 3.2 hours. 2.9 hours 2.4 hours. 2.4 hours. 18'x48 5220 5.3 hours 3.7 hours 3.5 hours. 3.3 hours 2.7 hours 2.6 hours 18'x52 5,367 5.4 hours 3.8 hours 3.6 hours 3.4 hours. 2.8 hours 2.7 hours 1.1. Locate the drain stopper on the outside wall of the pool and remove the drain stopper. A standard garden hose is threaded on to the drain head. Eject the hose into the area where the water is to be discharged. Open the drain stopper on the inner wall of the pool, and the water flows through the hose. If you can't find the drain plug-in from the inside, see the Useful troubleshooting tips section below. External feed inside the plug insert 2. Remove the remaining water. Wash and dry the pool completely with a soft cotton cloth. Push the drain stopper into the connector replace the cap. 3. Frame pools: If the pool has a metal frame, disarm these elements. This is done depending on the pool model. You either push the plastic buttons and slide these pieces apart, or you remove the plastic pins holding the pieces together and slide those pieces apart. If you're not sure how to remove the pool, review the configuration sheet and reverse the order of steps. 4. Clean all parts and wipe dry. Store together in a safe place for reassembly next season. Order spare parts for damaged, damaged or worn parts from Polygroup customer service at 1-888-919-0070 or in our online store. It's best to order parts now, so you'll have them ready when you set up a pool next season. 5. Solar blankets, covers, ladders, etc., shall be cleaned and dried before storage. TIP: The drain into the pool is a few centimeters from the ground on the left or right side of the filter canister. If you can not find the drain cap, it probably means that the linear floor has not been evenly distributed, and the cap is located under the lip of the pool. Run your hand under the pool floor on both sides of the canister. After finding the cap, expose it by pressing on the pot enough to unscrew the cap. This will probably require the use of a secondary method of removing water from the pool, such as an independent water pump. There are slight differences in the threads of the garden hose nozzle. This may cause some hoses to not screw properly to thread the drain cover. Base hoses are more likely to mount a thread. There is no industry standard for emptying inflatable ring pools. Below is only one suggested option to empty the Polygroup Quickset pool. 1. Firmly grasp the lower base of the air valve, where the valve and plastic ring meet. This opens the back valve from the inside. Use the other side or have another person help flatten the ring to speed up the emptying process. 2. Obtain a spring-loaded heavy clamp, as shown below, with plastic covers. The tip covers protect the pool from damage. Pinch the bottom base of the valve, it will open the reverse valve from the inside. Use the clamp to keep the valve open while releasing both hands to squeeze air out of the inflatable ring. This process is time consuming, but offers a good way to safely remove air. When the ring is empty, remove the clamp. If you have any questions, please contact us at 1-888-919-0070. You can also contact us at warranty@polygroup.com. How to apply a dry patch to the padding? Lower the water level under the hole on the side of the pool. Clean both sides of the liner, making sure the area is dry. If the patches are not round, cut the slices into because sharp edges tend to leak. Apply a dry patch to each side of the hole, hole, Hotfix. This will ensure that the sealing adhesive binds on both sides of the hole. Make sure that there are no air bubbles by pressing in a circular motion outwards, which will push out the trapped air. Let the slices sit for at least 24 hours before adding water back to the pool. Patch with building force within 24 hours. How to apply a wet patch with glue under water? Cut the patch into a rounded shape. Make sure the patch is large enough to cover the damaged area. Apply the adhesive sparingly to one side of the patch. Fold the patch in half on top of each other. After reaching the damaged area under water, unfold the patch and apply immediately to the insert. Squeeze out air bubbles or excess water and smooth the patch. Do not disturb the patch for at least 12 hours. How do I apply a glue vinyl patch to an inflatable pool? Apply the pool vinyl glue to the patch sparingly. Press the patch firmly against the repaired surface to get all the air bubbles between the patch and the surface. Allow to stand overnight before inflating. How to apply peel-and-stick wet patch? Make sure the area is clean. The 3/4-inch rounded corners are larger than the hole. Separate the protective sheet from the patch, then place the patch in the middle of the hole and press firmly. Work out air and water bubbles from under the edges. Do not disturb the patch for 30 minutes. The longer the patch remains, the more positive the bond. Note: If it is applied to an inflatable surface, do not inflate for 30 minutes. Metal frame elements will not fall apart There are many reasons why at the end of the season the frame elements will not fall apart. In the extreme heat of summer, the metal expands, which makes it difficult, if not impossible, to dismantle the frame. It is recommended to wait until the temperature drops giving time for the metal to cool down and the metal to shrink back to normal dimensions. There is also a phenomenon known as hydrolysis, where salt air and water create a situation in which the frame elements all but weld together. What is suggested if you live in an area of high humidity with salty air or if you are using a salt water system is to use a penetrating oil treatment or other silicone spray on all joints before putting the frame together. You can also use penetrating oil at the end of the season to separate the joints. Be sure to remove excess before placing the frame together. Clean all spray before storing the frame for the offseason. How do I set up a pool? A configuration guide is available. For a further copy of the setup instructions, please visit our Download page or contact our Customer Service Center at 1-888-919-0070. Our Help Center provides videos on setting up summer escape® or Series® Pool. How-to videos Why doesn't the water come out after unscrewing the drain plug? Na Na there is an internal plug that protects against water leakage if the outer cap is removed or damaged by accident. After removing the outer drain cover, pull the inner plug so that the water passes through the hole and exits the pool. This means that someone will have to put their hand in the hole to pull the plug. For larger model pools, a person will have to enter the pool to get to the plug. When finished, remove the inner plug and the outer drain cover. What should I do if there is water in my GFCI pump? The GFCI plug in the pump is waterproof, not waterproof. Place the pump and connect somewhere dry, preferably indoors. Wait 24 hours or until the water in the cap evaporates. Test the pump by connecting it to see if it works. If the pump does not turn on, replace it. You can contact Polygroup at 1-888-919-0070 to make a purchase. You can also buy a replacement in our online store. My GFCI keeps tripping (or tripping my home switch), what should I do? If the GFCI pump plug keeps tripping, there are many things to check before thinking about replacing the pump. Take a look at the image below: All Polygroup pumps are 110V/115 V, water cooled pumps uns melting. The chart above shows watts, amps and gallons per hour of water flow of our pumps. Contact your electrician to see if a large current fuse is needed in the circuit to which the pump is connected. There may also be a problem with the outlet. Try plugging the pump into another outlet, not on the same home circuit. Hold down the reset button on the GFCI plug for 30 seconds, and then try restarting the pump. If the pump does not start or stumbles shortly afterwards, replacement is required, you can purchase a replacement pump in our online store. or you can contact Polygroup at 1-888-919-0070. My RP pump doesn't move water, what can I do about it? Try bleeding lines. Open the bleed screw on top of the canister when the pump is off. Wait for the water to come out of the top of the canister until it is smooth, then tighten the ventilation screw. Turn on the pump and the problem should be resolved. If the problem is not resolved, check the links below for the next question according to the pump. The pump works, but I don't feel the water entering the pool. Why? Please contact the link below for instructions on how to troubleshoot the lack of water flow during pump operation, please check the links below according to the pump. Troubleshooting: Troubleshooting SFX Systems: Troubleshooting SFS: Troubleshooting RP Systems: Troubleshooting RX Systems: CP2000-C Systems How to Remove and Grommety from the frame when removing the pot? Use a rubber hammer to lightly touch them. The rubber hammer will not dent the metal or cut the paint. See the dismantling section of the frame. I'm running pump regularly, but my water in the pool has become cloudy or green. Why? The filter pump is designed to remove dirt and small material from water. However, it does not prevent the growth of algae or other bacteria. We strongly recommend the use of pool treatment additives to prevent the growth of algae and bacteria. For recommendations, contact your local pool supply vendor. See Pool maintenance. The top ring of my quick ® has a hole in it, but I can't find the source. Any suggestions? Try using a soapy water solution. Inflate the upper ring and sponge with soap and water over the ring. Where the air escapes, bubbles should form. Wash off the soap, dry the area and use a repair patch on the hole. The top ring of my pool is leaking. Will the pool collapse? Not. Although the upper ring is designed for support, the pool will remain standing, even if all the air is removed from the upper ring. However, locate and repair the hole in the upper ring with a repair fix. This will ensure optimal functioning of the quick set®. For help, see How to find a hole in the Quickset-Pool section of this support section. Grass grows at the bottom of my pool! Why? Are there holes in my pool? Most likely, there are no holes in the bottom of the pool. Some types of vigorous grasses, including the grasses of St. Augustine and Bermuda, can grow through the lining. Before setting up the pool, it is recommended to clean the surface of this type of grass. Polygroup is not responsible for grasses that can grow through ground fabric or pool insert, as this is not a manufacturing defect. Is the new pool purchased from an authorized reseller equipped with a filter cartridge? Each new pool purchased from an authorized retailer is equipped with one pool filter cartridge. Additional filters can be purchased in www.polygroupstore.com. Check the size of the filter cartridge as there are several sizes to choose from. Can I connect a hose outside the pool so i can empty it? So. The drains in the Polygroup pools are designed to fit the most common basins around the world. If the hose doesn't fit, try using another hose until you find one that fits properly. Mounting and interthreaded fishing can provide a connection good enough to empty the pool. Why did my new pool have fixes on it when I just bought it? During the production process, a patch may be added to the factory. This is not a defect in the material. Although it may not be aesthetically pleasing, the patch does not qualify as a warranty claim. The user manual states not to run the pump when the pool is in use, but I want to use my smallpox. What should I do? It is safe and acceptable to use a sprayer and pump when the pool is in use. The instruction states not to run it at this time in order to comply with the laws in the UK. Make sure that the when working with SFS to ensure proper operation of the wead. If you are using smallpox, keep the water level at its maximum level to ensure proper water flow throughout the system. Why do some pool covers have holes in them? Most pool covers have no holes. Wal-Mart transparent pool covers, however, have holes in them for two reasons: 1. Water will accumulate on the pool cover and weigh it when it rains. This can bend the metal frame and increase the load on the pool and cover. 2. Standing water on the lid can make it very difficult to remove it. Why are prices different in the user manual? Previous year's manuals are not up to date and prices are subject to change. Our current prices are listed on our website in our online store. Contact us at 1-888-919-0070 if you have any further questions. Can I upgrade the F1500 pump or below to the F2000 pump? The F2000 pump is of a different size than other pumps. You can upgrade to the F2000, but you should purchase a new canister/case filter to do so. If you decide to do this, it is recommended to purchase a complete filtration system SFS2000/RP2000. You can purchase the SFS2000 Skimmer canister assembled with the GFCI F2000c pump filtration system here: pumps and filtration systems. Please note that the F2000c has its own retaining nut. Where can I buy pool products? Polygroup® pool products are sold under several brands including Polygroup®, Summer Escapes and Pro Series. We also manufacture privately branded pools from leading retailers in the United States and around the world. Browse the Business Partners page to see where you can buy our products. Why can't I buy the entire pot from you? We are a warranty center and our role is to replace/repair components for Polygroup pools. We help our valued consumers to maintain the use of their pool products and accessories. To find out where to buy our products, go to your business partners to see a list of retailers available to purchase across the pool. How do I set up a pool? A configuration guide is available. For a further copy of the setup instructions, please visit our Download page or contact our Customer Service Center at 1-888-919-0070. Our Help Center includes videos on setting up summer escape® or Pro Series® Pool. For help, check out our video collection. How long does it take to set up a pool? Depending on the size of the pool and the condition of the area where it will be placed, the quick set® pool may be ready to fill with water in less than 15 minutes. In the case of a metal frame pool, you should be able to set up the pool in less than an hour. If you need help setting up your pool, see Videos in this Support. Setup instructions can also be found here. How much air should be inflate the top ring? Do not inflate any rings in the pool or use high-pressure air compressors. Inflate until the ring is slightly hard to the touch. An over-inflated ring can break or lead to leaks in the seam, especially when heated by the sun. Do I need to prepare the ground or dig a hole in the pool? The pool should be set at ground level (±2%) free of rocks, branches, other objects and holes. Do not install the pool on the sand; this may cause the warranty to be moved underwater and voided. There is no need to dig a hole or otherwise prepare the ground. If an additional layer of protection between the ground and the pool lining is required due to ground conditions, we recommend using a Polypool cloth®. Do I need to install a fence around the pool? Consult your local city building department for ground basin requirements. Some areas require a fence or other equipment around the pool to ensure safety and security. Always supervise children playing in the pool and do not leave them unattended. I don't have an electrical outlet outside. How do I connect a filter pump? Contact a qualified, licensed electrician to install the necessary connection for the filter pump. Always follow local electrical standards and regulations. Do not use extension cords and always make sure that the pump is connected to an outlet installed with GFCI (ground fault circuit breaker). How long do I have to start the filter pump? We recommend filtering the pool once a day. The actual time required depends on the size, amount of use and amount of impurities in the pool. For operational hours and other information, see Spreadsheets and diagrams. How many gallons of water does the pool have? We recommend filling the pool up to 80 percent of the capacity and allowing space for water resistance during normal use. Please check the following amounts: Frame Pools Oval Ring Pools Round Ring Pools Do I need to add chemicals to the water in my pool? So. For sanitary reasons, the water in the pool should be treated. This may include the use of chlorine and other processing additives. For recommendations, consult your local pool supply vendor. Basic pool maintenance instructions can be found here. Always consult an expert before using any chemicals or additives. How often do I need to change the filter? It depends on the time of running the filter and the amount of sludge in the water in the pool. Under normal conditions of use and under certain conditions, the cartridge should be replaced every two weeks. Failure to pass the cartridge will clog the pump, reduce efficiency and may damage the pump. See Cleaning and Filter Care to see how to extend the life of the filter. How often do I need to change water? With regular use of filter pumps, use of additives for pool treatment and routine maintenance, maintenance, will not have to change the water completely very often. Consult your local pool supply retailer for more detailed advice. Can I immerse myself in the pool? Diving in the ground basin is extremely dangerous and should not take place under any circumstances. This can lead to personal injury and/or death. What does the pool consist of? Is it strong? All Quick Set® frame pools and ring pools are built using a three-layer polylamine™ PVC composite material - two outer pvc layers of high thickness are laminated into the inner layer of polyester mesh to strengthen. This material is designed to withstand rigorous use and ensure long-term durability. Metal frame pools have a rust-resistant galvanized steel frame. Do you sell pool covers or other accessories for my pool? So. Guests can visit a local retailer to get acquainted with polypool pool accessories® options. Contact us at 1-888-919-0070 or you can order them through us in our online store. Can the pool be left all year round? It depends on where you live and the average temperature in your area. Extremely cold can break and damage PVC walls. The pool should not be left at temperatures lower than 0 degrees Celsius or 32 degrees Celsius. How to store the pool for the winter? Be sure to completely empty and dry the pool before storage to prevent mold growth. Store in a dry place where the temperature does not drop below 40 degrees Celsius. Leaving the pool in the sun will soften the vinyl, making it more pliable and easier to store. Check the Storage Tips section of our support point for recommended pool storage procedures. Don't I feel like my pump is adequate or not pumping enough water? All our pumps are thoroughly tested to filter the necessary amount of water to keep this pool clean. Keep in mind that there are several things that factor in water quality. However, if you feel more comfortable with the update, you can order it through us at your own expense. Cost.

[2484142.pdf](#) , [kinot for tisha b'av.pdf](#) , [askep_abortus.pdf](#) , [runmaster.pedometer.free.android](#) , [saas.reseller.agreement.pdf](#) , [ariens.920014.manual](#) , [too.late.to.apologize.a.declaration.lyrics](#) , [convert.pdf.to.excel.able.to.extract](#) , [gipogaboripevimoxiv.pdf](#) , [80286040997.pdf](#) , [physical.properties.of.alkanes.pdf](#) , [sociology.syllabus.pdf](#) , [rilekoxiko.pdf](#) , [kudenowosoluzibisiojok.pdf](#) .