




I'm not robot



[Continue](#)

Black desert wizard leveling guide

1 2 Table of Contents 3 4 5 6 7 8 10 11 12 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 This website or its third-party tool use cookies, necessary in its functioning and required to achieve the reason shown in the cookie policy. If you want to know more or withdraw your consent to all or some of the cookies, please refer to the cookie policy. By closing this banner, scrolling this page, clicking on a link or continuing to browse otherwise, you agree to the use of cookies. Return to Commercial & Vehicles Info Magnetic Type Full Rotary Hook Free Arm Skeleton Body Construction 9 Stitches Including Boutonhole 4-Step Button Maximum Zi Width: 5 mm Maximum stitch length: 4 mm Lay-in Wire Tension Control Extra-high Press FootAge Lift Marking on Needle Bottoms (Inches and Metric) Automatic Clutch Bobbin Sale Snap-On Presser Thread Cutter Silt Wire Lead Takes Up Horizontal Spool Piol Lamp Power Switch Controller Important SAFETY WHEN using an electric device, basic safety safeguards should always follow, including the following: This sewing machine is designed and manufactured for home use only. Read all instructions before using this sewing machine. HAZARD— To reduce the risk of electric shock: 1. A device should never be left unprotected when plug in. Always discover this sewing machine from the electrical grip immediately after using and before cleaning. 2. Always unplug before replacing a sewing machine bulb. Replace bulbs with same type rated 15 watts. WARNING—To reduce the risk of burn, fire, electrical trauma, or injury in person: 1.Do are not allowed to use as a game. Turn off necessary attention when this sewing machine is used by or near kids. 2.Use this device only for its intended usage as described in this property manual. Use only attachments recommended by the manufacturer as contained in this property manual. 3.Pa ever operates this sewing machine if it contains a damaged cord or plug, whether it's not working properly, whether it's fallen or damaged, or falling into water. Return this sewing machine to the nearest authorized dealer or service center for examination, repair, electrical or mechanical adjustment. 4.Pa ever operate the device and any time opening is blocked. Keep opening ventilation of this sewing machine and controlling feet free from accumulation of ties, dust and coated fabric. 5.Pa ever drop or insert any object into any openings. 6.Do not used outside. 7.Do by operating where aerosol (spray) products were used or where oxygen is administered. 8.To unhide, turn all controller into cut (O) position, then remove the grip plug. 9.Do unplug by pulling on cord. To unplug, plot the outlets, not the code. 10.Keep fingers away from all moving parts. Special care is required around the sewing machine needle and/or blade cutting. 11.Always use the plate needle. The evil plate can cause needle to break. 12.Do don't use the blessings. 13.Do do not pull or push fabric while sewing. It can distort the needle that causes it to break down. 14.Switch this sewing machine off (O) when making any adjustment in the needle area, such as the needle wire, change the needle, coil wire or change the press foot, and the likes.15.Always unplug this sewing machine from the electrical grip when removed cover, Lubrication, or when making any other adjustments mentioned in this property manual. use of the device in a safe manner and understand the dangers involved. Children are not playing with the device. Cleaning and user maintenance must not be performed by children without supervision. To outside Europe (except U.S. A and Canada): This device is not intended for use by individuals (including children) and reduced physical, sensory or mental ability, or lack of experience and knowledge, unless given supervision or instruction regarding the use of the device by someone responsible for their safety. Children must be supervised to ensure they do not play with this device. Please note that upon disposal, this product must be safely recycled in accordance with relevant National legislation related to electrical / electronic products. If in doubt please contact your retailer for guidance. (European Union only) Manual Instruction Manual Two Handbook Turn D'DInstructions IMPORTANT IMPORTANT SECURITY Instructions This Device is not intended for use by individuals (including children) and reduced physical, sensory or mental ability, or lack of experience and knowledge, unless provided supervision or instruction regarding the use of the device by a person responsible for their safety. When using an electrical device, basic safety safeguards should always be followed, including the following: This sewing machine is designed and manufactured for home use only. Read all instructions before using this sewing machine. Hazard— To reduce the risk of electric shock: the 1.An should never be left without intended when the plug-in. Always discover this sewing machine from the electrical grip immediately after using and before cleaning. 2.Always unplug before replacing a sewing machine tampon. Replace bulbs with same type rated 15 watts. WARNING—To reduce the risk of burning, fire, electrical trauma, or injury in person: 1.Do not allow children to play with the car. The machine is not intended for use by children or disabled people without proper supervision. Not allowed to be used as a game. attention is necessary when this sewing machine is used by or near kids. 2.Use this device only for its intended usage as described in this property manual. Use only attachments recommended by the manufacturer as contained in this property manual. 3.Pa ever operates this sewing machine if it contains a damaged cord or plug, whether it's not working properly, whether it's fallen or damaged, or falling into water. Return this sewing machine to the nearest authorized dealer or service center for examination, repair, electrical or mechanical adjustment. 4.Pa ever operate the device and any time opening is blocked. Keep opening ventilation of this sewing machine and controlling feet free from accumulation of ties, dust and coated fabric. 5.Pa ever drop or insert any object into any openings. 6.No used outside. 7.Do by operating where aerosol (spray) products were used or where oxygen is administered. 8.To unhide, turn all controller into cut (O) position, then remove the grip plug. 9.Do unplug by pulling on cord. To unplug, plot the outlets, not the code. 10.Keep fingers away from all moving parts. Special care is required around the sewing machine needle. 11.Always use the proper needle plate. The evil plate can cause needle to break. 12.Do don't use the blessings. 13.Do do not pull or push fabric while sewing. It can distort the needle that causes it to break down. 14.Switch this sewing machine off (O) when making any adjustment in the needle area, like the needle thread, change the needle, coil wire or change the press footage, and the like.15.Always unplug this sewing machine from the electric grip when removing the cover, lubrication, or when making any other adjustments mentioned in this property's manual. SAVE THESE DESIGN INSTRUCTIONS and the specifications subject to change without a previous notice. Please note that upon disposal, this product must be safely recycled in accordance with relevant National legislation related to electrical / electronic products. If in doubt please contact your retailer for guidance. (European Union only) I IMPORTANT ENSTRUCCIONES OF SEGURIDAD Cuando seutiliza un aparato electrico east necessary tomatto ciertas precaaciones basicas de seguridad, como las siguientes: lea today laser instructions topped two aparato use. PELIGRO - Para reducing el riesgo de electric choice: 1.No nunca el aparato sin vigilancia mientras styled enchufado. The simple desenchufe máquina de la tomas electrica despues two utilisarla users nearby limpiarla. 2.The desenchufe máquina cada vez vaya a canbilla bombard. The Cambie Panbilla porous otra del mismo tipos (15 W). AVISO - Para reduced el riesgo de quemaduras, shock quemaduras, eléctrico eléctrico oidas a person: 1.No deje natilice utillce la máquina fuera fuera. Bost the special attention cuando or teary children. 2.Use the device only for use to describe in this user manual. Use of only accessories is recommended by the manufacturer and indicates in this user manual. 3.Pa never use this sewing machine if you have a bad plug or cable, whether it's not working properly, whether it was hit or damaged, or if it fell into water. Send this sewing machine to the nearest store or maintenance center if it needs to be examined, repaired, or subject to electrical or mechanical adjustment. 4.No never use the device if any slits are blocked. Keep the slits routes in this sewing machine with free pedal pedals to link, dust and cloth fabric. 5.No to drop or insert any type of object into any openings. 6.No used outdoor motor vehicles. 7.No used machines in which aerosol spray products are used or where oxygen is administered. 8.To dispel, put all CONTROLLER OFF (O) and unplug the machine. 9.No pull the cable to wrap. To open the outlets, not the cable. 10.Keep your fingers away from all moving parts. Take special care around the sewing machine needle. 11.Always use the appropriate needle plate. Correct patches can cause needle to break. 12.No a lowered needc. 13.No pull the canvas or push it while you sew. The needle could deflect and fence. 14.Turnen this sewing machine (O) every time you have to make adjustment in the needle area, like the needle thread, change the needle, thread the curve, change the press footage, and similar operation to .15.Unplug this sewing machine each time you have disastrous cover, fat, or make any other settings mentioned in this user's manual. KEEP THESE CONCEPTION INSTRUCTIONS and the specifications subject to change without notice. Please note that for the destruction and/or recycle of this product you must follow the rules of national legislation on electrical and/or electronic products. If in doubt asking your dealer. (European Union only) II CRUCIAL DESIGN OF SECURITE USABLE ELECTRICAL APPARATUS. FAIR APPEARANCE RESPECT LESS DESIGN OF FUNDAMENTAL SECURITY. NOTATION LESS DESIGN FOLLOWING: AVANT d'usage cset cage device, glasses cease instruction. DANGER: Pour Ereduire less risky d'electrocution. 1.II laser beam laser jamaica until without monitoring lorsqu est branched. II faints are hurting to digest drivers' cars from the murale electric price, apr your son is adventurous from the lanettoyter. 2.II faust is making the car sales débrancher from replacing light bulbs. Replace the bulb with a bulb of the same type 15W. WARNING: To reduce the risk of burning, fire, electroction or personal injury: 1.II should not use the vehicle as a toy. Be very caution when this sewing machine is used by or near kids. 2.Use this machine only for intended usage, as described in the sewing machine manual. Use of only accessories is recommended by the manufacturer as indicated in the sewing machine manual. 3.II never would operate the sewing machine if the cable or socket is damaged, whether it's not working properly, whether it's falling, whether it's damaged or if it falls into the water. Returns the sewing machine to the nearest store or repair center for examination, repair or electrical or mechanical adjustment. 4.II would never operate this vehicle if the belly are plug. Keep the stomach of this sewing machine with the free crowbar cursor in any accumulation of faf, dirt and piece of clothing.5.II should never drop or insert objects in both of them. 6.II should not be used outside. 7.II would not operate if aerosol products (vaporizers) are used or if there is an oxygen system. 8.To unplug it, turn the switch into the stop position (O), then remove the car by pulling the cable. To unplug it, there's time to get the socket, not the electric cable. 10.Keep your fingers away from all moving parts. Be especially careful in the area near the needle in the sewing machine. 11.II should always use the correct needle plate. If the needle plate is not appropriate, the needle can break. 12.Do does not use needle curve. 13.No pull or don't push the tissue during puncture. This can cause the needle to disturb and cause it to break. 14.Before making adjustment to the needle area such as threading the needle, wire the case or change the browser, etc. set changes to the sewing machine on clauses (O). 15.Always unplug the sewing machine from the electric grip before removing the hands, grease it or make any other adjustments mentioned in the sewing manual. KNOW CONCEPTION NOTICE and features are subject to change without prior communication According to the national legislation precept producing doit's pertaining energy reclaimed energy apparatus accords less forecasted to pour less electrical or electronic devices. Enable cas de contact voting revendeur of the sewing machine. (sealed europeenne) III SECTION 1. NAME OF THE PARTIAL PARTY NAMEnot to... be a bigger part of the party. 6 Standard Accessories..... 6 carrying sleeves...6 ing sleeves. 6 SECTION 2. GETTING READY TO SEW Connecting Machine to Power Equipment For... 8 Before you use your sewing machines..... 8 For thy safetynot so... 8 Managed Sewing Speed..... 8 Setting Spool Pins..... 10 Presser lifter feet.....not good. 10 Change press footage..... 10 Change Useless..... 12 They check needle..... 12 Threads and needle charts..... 12 Bobbin advanced 14-16 Wire drill in 18 Drawing up thin bobbins 20 Needle Threader 20 Balanced Needle Thread Tension..... 22 Stitch Selected Models 24 Stitch Chart Panel 24 stitch hand length..... 24 Adjust stitch stitch..... 26 Stitch Wide Dial.....not so... to... 26 Reverse Stitch Buttons 26 Bringing plates 26 SECTION 3. Basic sewing straight stitch..... 28 To change the direction of sewing 28 Variable Needle Positions..... 30 Seam Guide Line..... 30 Turn a square corner 30 Basic Zigzag 32 Tricot Stitch..... 32. 32 Straight Jerk Stitch 34 Zigzag Jerk Stitch 34 knit stitch 36 Sewing Buttons..... 36 Automatic buttonhole..... 38-40 Corded Boutonhole..... 40 Corded Boutonhole..... 40 Pin Bucking 46 Free Menus and Encryption 48 blind Hem Stitch well, if you're 48 years old. 50 SECTION 4. STITCHES DECORATIVE crankings.....not so if you can get something quick. 52 Works 54 Applications..... 9..... 54 applications. 56 stitch boxes 56 Decorative Model Stitch..... 58 Stretch Model Stitch..... 58 SECTION 5. CARE IN YOUR CAR Clean the Bobbin case and the craft race..... 60 Clean the dog food..... 60 Elbows fixtures.....not so... to 60 of elbows of light... 62 Troubleshoot 64 SECTION 1.NAME OF THE PARTY NAMES OF THE PARTIES..... 5 Extra tabs..... 7 Standard Accessories..... 7 sleeves. 7 SECTION 2. THE COSER PREPARATION Connects the machine to the power cord..... 9 Before you use the sewing machine..... 9 For your safetynot so... 9 Sewing Speed Control..... 9 Prepare real pins..... 11 Presser levers foot levers. 11 Tree Changed..... 11 Needle changes..... 13 To check needle..... 13 Selection of threads and fabrics..... 13 brush widths 15-17 Thread Threading Machine in 19 How to pull out the wire from the marble 21 Needle insarmer 21 Compensation of blood-wireless needle tension..... 23 Stitch Template Select 25 Stitch Illustration Panel..... 25 length stitch length..... 25 Elastic custom adjustment..... 27 Stitch Wide Picks 27 Return sewing keys..... 27 Left-hand plates 27 SECTION 3. BASIC COSTIURA straight stitch..... 29 To change the sewing direction..... 29 Variable needle position..... 31 Sewing Guide Lines..... 31 Turn a square corner 31 Basic Zigzag 33 Zigzag in point..... well, to... 33 Straight Elastic Stitch. 35 Elastic Zigzag Stitch 35 Knitting stitch35. 37 Elbow 37 Ojal auto-tico..... 39-41 Ojal acordonado 43 Cremaller's Application..... 45 alforzas.....no need to... be a good one of the other. For the first 100 or the other, the first of the other. For the first consecion of the other. For the first 100 or the other, the first one to whom the other had the first 100 or the other. 47 Remiendo a very kodo mano 49 Dobladillos versus invisible puntada..... 51 SECCION 4. PUNTADAS DECORATIVAS Puntada de onda..... 53 fruncido... 53. For the first 100 or the other, the first one to the other. 55 Application 57 Puntada de caja 57 Puntada de 57 Localizacion are solutions averas... 65 SECTION 1. NOMS OF PIECE NAMES IN THE PIECES..... 5 Extensions tabs 7 Standard Accessories..... 7 transport sleeves..... 7 transport sleeves. 7 SECTION 2. READ MORE connected machines to power supply..... 9 Before you use your sewing machine..... 9 For your safety.....not so. 9 Control of sewing speed..... 9 Fixing the real doors..... 11 escalate and lowered the crowbar.....not to... 11 Change to crowbar..... 11 The needle changes 13 Needle control 13 Table of Threads and Needle..... 13 Complete the can.....not so. 15-17 Wire Threading Machine in 21 Needle threads.....21 needle wires. 21 Putting a needle's thread tension 23 Choosing from point template..... 25 Panel of drawings in dots..... 25 Points length of dial 25 Setting the point is extended..... 27 Dial Width point..... 27 Reverse button..... 27 Pick up plates..... 27 SECTION 3. BASE OF THE SEAM POINT. For the first 100 or the first of the other. 29 How to change the direction of elbows.....not to... 29 Variable needle position..... 31 Sewing Guide 31 Vire nan ang dwa 31 Zigzag senp 33 Senp knitting pwen 33 Dwat pwolonje pwen 33 Dwat pwolonje pwen 35 Zigzag ekstandib pwen 35 Wool knitting pwen 37 Bouton seam 37 Otomatik bouton..... 39-41 Bouton yo bouton 43 Zipper femem 45 Pling 47 Grats reparasyon ak anbwochaj..... 49 envizib wonte 51 SEKSYON 4. Pwen DEKORATIF ak koki 53 emosyon..... 61 Netwaye ekipaj fomasyon in 61 Netwaye Lightng nan seam la 63 Nan ka nan difikilte 66 mwen 10 o 11 12 13 14 15 16 17 17 18 '0 '5 '6'7 '8 e r q '21'4'3 SEKSYON 1. NAMES OF PARTS Names of Parts q Stitch pattern selector dial r Stitch length dial e Stitch width dial r Reverse stitch control t Bobbin winder stopper y Bobbin winder spindle u Spool pins i Stitch chart panel o Bobbin winding tension disc tThread guide t1Thread take-up lift t2Thread tension t3Face cover t4Needle thread guide t5Needle flat t6Extension table (Accessory box) t7Carrying handle t8Handwheel t9Power switch t10Machine socket t11Free-arm t12Presser foot lifter t13Needle t14Needle clamp t15Presser foot holder t16Screws t17Presser footbal t18Foot control SEC SEC 1.NOMBRES OF LAS PARTES Numbers of las partes q Selector del diseo de puntadas u Selector de longitud de puntada e Selector de ancho de puntada r Mando de inversion de puntada t Freno del canillero y Eje de la canilla u Pasadores portacarretes i Panel ilustrativo de puntadas o Disco de mition de coainado de la canilla tOgua del hilo t1Palanca tirahilos t2Selector de tension del hilo t3Tapa frontal t4Ensrartador de agujas t5Placa de aguja t65Mesa supletoria (estuche de accesorios) t7Asa t8Volante t9Interruptor t10Toma koripsyon t11Brazo gratis t12Palanca del elevacion del tal prensalip t13Aguja t4Tornillo ajiste de mition t5Soporte del pwezante t6Tornillo de fijacion t7Pie prezante t8Pedal SEKSYON 1. NOMS NAN NON MOSO nan pati q Chwazior Your Model Point To Length Dial Point Wide Dial t Rear-Step Control Reel So reel are Reel u Reel Door i Panel at drawing point o can spool disc tension tO Guide-wire t1Tire-wire t2Pure voltage chart t3Capot before t4Enfile-needle t5 Extension (accessories box) t7 Transport control t8Volant t9Interruptor t10Prise of the t11Bras free t12Relevage cleaning of t13Aiguille t14Vis Needle t15Support to make t16Vis fasten t17Pie t18Commande t18Commande in the foot extension – Detach the table from the machine, illustrated, for free arm sewing in cups and sleeves. The extension table can be used as Props box. Attach the table to push the extension table until it snaps to the machine. q W Standard Accessories Q Bobbins W Needle Set and Zipper foot and r Blind Hem stitch foot t sliding foot buttons open buttons / Seam ripper u Screwdriver (small) sisters i Darning plate ul Bring Press down the thermal handle to bring increase the carrying handle. q Carry Busy Q Mesa supletria - Unshared e la mesa para cosido de puos orgasm can ravings, pulled from the mevil afuera de la la maquina tal tal commodity stem at the liltrason. La Mesa de extrion puede utilizar como kaja props. Assembly de la mesa empuje la la mesa supletoria que the makeup engineer. Tab Extensions - Remove the Tab Capture the table from the machine, as illustrated, for sewing with free arms to the wrists and sleeves. The extension table can be used as storage for accessories. Hang the Push tab to the extension table until it hangs in the machine. Accesorios es-ndar qar canillas or Juego de agujas de cremallera r Pie de dobladillo kontada invisible t main by ojales automatico are abridor de ojal/rasgador de kosturas u Destornillador (pequeo) l placa de z Asa Presione ace mark q Asa Standard Accessories Q Canettes W Needle toys and feet zipper r Invisible foot t sliding footon buton button button / Takeover u Tournevis (small) l Pick-up Shipping plate Handle the marks in the handle wearing its lift handle. q Trnsapo handle SECTION 2. GETTING READY FOR SEW TW connecting machines in Power r Supply Q e CAUTION: Before linking the power cord, make sure that the voltage and frequency are shown on the vehicle's conform to your electric power. 1. Close the change of power to change Q.w to 2. Put your plug machine in the machine grip e. 3.Insert equipment to plug the power plug r in t. 4.Turn on the Q to change the power to the activated and elbows of light. q Power Switch you plug machine and Machine plug r power supply plug before using your sewing machine before using your sewing machine for the first time, put a dump underneath the press foot and run the machine with wires for a few minutes. Drying oil may appear. For Security *While in Operation, always keep your eyes on the elbow area. Do not touch any moving part, such as wire take-up levers, doors or needle. * Always turn off the power switch and unplug from the power equipment - When leaving the machine unprotected - When attaching or removing any part – When cleaning the machine * does not place anything on the foot control, when they are not sewing. Managed sewing speed can vary by the foot control. The harder you weigh on the foot control, the faster the car runs. SECTION 2. PREPARATION FOR COSER Connecting machine to power cord CAUTION: Before connecting the connected cable to the mains, make sure that the voltage and frequency of the machine, shown on the name, match those of the network provided in your home. 1.Turn on the Q switch. 2.Insert the plug in your car into the power grip e. 3.Put r to power stringer plug in the t. 4.Turn on the Q switch to activate the power passage and the elbow lamp. q Switch you plug machine with power grip r Power cord plug t socket section 2. PREPARE COUDRE Branchman de la car feeding machine UST: Avant leach hooks, ensuring v-oue voltage que indication machine corresponds to a type of safety courtesy. 1.Eteigne z l appliance que. 2.Inserez electric car bulb cost from the your car. 3.Inserez relaxes electric ballet fine r. 4.Basculez it interruptors q pour aligning machine and allow it irregurys from the future. q Interrupters walk /ar by going Fiche two machines and Prising the two car r Fiche d'Alignment t Prae Before using the sewing machine before using your sewing machine for the first time, put a piece of fabric test underneath the foot press and pass it to the machine and wire for a few minutes. Remove any oil that may appear with a canvas. Avant d'utiliser votre machine? coudre avant d'utiliser votre machine? Coudre to pour out the premi's fois, the morceau oiled backdrop collector denied pied nails and guildist machine lane high duc pendel quelant minutes. Essayez reads flrt peutil devices. For your security *While in operation, always look at the elbow area. Do not touch any of the moving parts, such as the wire levers, gates, or needle. *Always close the change and del alimentation cable: The Cuban defence of the makeup sin -Cuban sin is quite a part alguna party -Cuban maquina no coloque nada maan mausoleum el pedal cuando northern stress cosiendo. For your safety – During operation, always observe the elbow area. Do not touch any moving parts, such as the wire zoom, steering wheels or needle. Always lock the device and unplug it in the electric socket: - If the machine stays unprotected - Secure or removes parts - To clean the machine - do not put anything on the foot control if you are not sewing. Control of velocidad de costura la velocidad of costura puede varies median ammonun pedals. Cuban fuerto ms president el pedal, the rapidamente me: ira makeup. Sewing speed control the foot control allows the elbow speed to vary. The more you press the foot control, the faster the sewing machine. Setting Spool Pins pints are used to keep the shoulder of wires when eating the wire in the machine. For use, pull up the talor pin. Push down for storage. q Upper Thread or Pit Tangle NOTE: If you are using wires that tend to tang around a wooden pin side, q wire in the pin hole of pin cups as shown, and the wheel should face the side wire, and d q w e Presser Peter Lifter Left raise leverage and lower the foot press. You can increase it to about 1/4 (0.6 cm) above the normal position up helps place heavy fabric under the foot. Q Presser lifter foot or Normal up higher position switch foot Press Foot Press Foot wroove e Pin CAUTION: When attaching or removing press foot, closing the power switch. To remove the laptop's turn towards raising the needle bar at its highest position. Expand the press footage. Push the toe into the pressing stone q to handwriting it to the foot holder. To attach the foot press so that the comb and on the foot lines are directly below the groove or in the footer holder. Lowered overnight holders closed the foot to place. Preparation of pasadores portacarretes los pasadores potacrete is the utilising paragan loss of portrait del Hilo cuando is in the back of a large makeuy. Para hacer noor two lost pasadores portacarretes, lev-netlos. Avitelos para al almacenaaje. q Hebra de la bobina or agujero e Hilo enredado NOTA: Cuando seutilice un hilo tend to tend a pasador del pasador portacarretes and, unhested por el agujero or del pasador taly como muestra the image highlights. El agujero debebe early encardado con el pasador del Hilo Reel doors fixing the real doors they used to keep the nails of wires that power the car. To use them, pull them up. Lowered them for storage. q Top thread or Gatch e Knot NOTE: If you use a thread that tends to tang around a real holder pass it in the hole of the real holder as they represent. The fore also must face the spool wire. Palanca del Elevacion del Pie Prensatelas La Palanca del elevacion del pie main are Baja el mismo. Puede sibir already of 1/4o (0.6cm) insimal por de posicion of paralytic insecticide habit insecurity of tejidos debajos del pie. q Palanca de elevacion del pie main or posicion elevada normal ms alta Cambio de main Q Pie Prend W Ranura e Pasador PRECAUCI-N: Cuando a 'o well positioning ammonun pie, apag (OFF) switchor el. Para extraerlo Gire el volante hacia usted para-aguja to a social ms alta. Suba el prensatelas pie. Shooting el pie featuring qpara left qpara. Para montarlo Coloque el pie prensatelas de modo el pasador and del pie debajo de aline de ranura del soporte del Pie. Baje el soporte del pie paraj el main ma su lugar. Expand and miticate the lifting levers of the navigation browser to lift the libe and lower the crowbar. You can lift it to 0.6 cm (1/4) above the high normal position to put a thick tissue under the foot.q Get up to the browser or High Position normal and Maximum Position Change of crowbar q Doe foot rainure and Pawn WARNING: To attach or remove a crowbar, turn the switch on stop. Unsemy Turn the Wheel's towards you raising the needle bar at its top position. Elevate the navigation. Push the finger into the doe tree q to remove it from its support - Install the browser set so that the axle of the foot aligns directly below the groove of foot support. Lower foot support closes the foot in place. Change Need to Caution: When changing needle, turn off the power switch. Increase the needle by turning the hand towards you and lowering the lower foot. zLoosen screws the clamp needle by turning it counterclockwise. Remove needle from the clamp. xInsert the new needle in the clamp and the side of the dish away you. When putting needle in the clamp, push it up as far as it will go and tighten the firm's screw caps and the screw driver. To check the Needle Plate the side of the needle on something flat (needle plate, glass etc.). Clearly between needle and flat surfaces should be consistent. Never use a bent needle or blunt. Wire and Needle Fabric Chart Wire Size Light Crepe from China, Sall, Fine Silk 65 (9) Law Weight, Organdy, Fine Cotton or Georgette, Fine Synthetic 75 (11) Tricot Fine Coton Covered Polyester Medium Linens, Cotton, Piqué, 50 Eithr 75 (11) Serge, Double Knits, 50 to 80 Cotton or Percale 50 to 60 90 (14) Cotton Honesty Cover Lou Denim, Tweed, 50 Night 90 (14) Cotton Cover Heavy Denim, Tweed, 50 Night 90 (14) Cotton Cover Heavy Denim, Tweed, 50 Night 90 (14) Cotton Cover Polyester Heavy Denim, Tweed, 50 Night 90 (14) Synthetic cotton cover heavy Denim, Tweed, 50 night 90 (14) Cotton covered polyester Heavy Denim, Tweed, 50 to 60 90 (14) Synthetic Cotton Cover Lou Denim, Tweed, 50 to 60 90 (14) Synthetic Cotton Cover Heavy Denim, Tweed, 5 Gabardine Bean, or Suit, Drapery with 40 to 50 Cotton 100 (16) Upholstery Fabrics 40 to 50 Synthetic Cotton Cover Polyester * Overall, Fine Wire and Needle are used for thinner stiper, and thinner wire and needle are used for heavy sewing fabric. * Always test threads and needle sizes on the fabric slice that will be used for the actual elbow. * Use the same wire for needle and bobbin. * When sewing stretches, fabric is very fine and synthetic, use a stretch needle. A needle stretch effectively prevents jumping seams. Needle Switch CAUTION: When changing needle, turn the OFF switch. Lift the needle by turning the wheel toward you and lowering the press foot. zTurne needle clamp's screw counterclockwise. Removes the needle from the clamp part. xIntroduce the new needle in the flag and hand side of the flat face back. When putting the needle in the flange, push it upwards bottles and firmly tightly screw the needle with the screwdriver To check the place needle the dish of the needle on something flat (needle plate, glass, etc.). The gap between needle and the flat surface should be consistent. Never use a needle or handgun. Wire and canvas selection * Overall, fine thread and needle are used to sew fine fabric and for thickness, thick wire and needle as well. * Always check the wire thickness and needle size on a small cloth to be used in the season. * Use the same wire for the needle and knob. *When sewing is very thin with elastic fabric, use an elastic needle. An elastic needle effectively prevents custom jump. Fabric Needle Fabric Needle China Crepe Thickness, Fine Silk, 65 (9) Light Voile, lawn, fine cotton, organism, synthetic cotton 75(11) georgette, fine tricot, polyester covered in fine cotton thickness bed, silk 50, 75 (11) half cotton, piqué, cotton 50 to 50, or sharply, polyester meets 90 (14) double, pecal cover of cotton synthetic 50 to 60 thickness, Silk 50, 90 (14) tweed head, cotton 40 gabardine, 50 suits, polyester 100 (16) checkout, curtain cover and with cotton autostectic fabric synthetics 40 to 50 Change d'clay ATTENTION: Alien vehicles pour change d'agille. His rose aiguille highlights the tournant volant straw straw and abaisse pied on the b. zDesserrez's screw from serage from its aiguille one night fence means fence fence to two clay d'ine displays. His retirement aiguille de saxation. xInszrez lavelle aiguille dance saxation, when tucked into two vous dish. Lors from elections he aiguille the green fixation, the booklet loin aussi loin possible and sedate ace screw stanchion from fixation above screwdriver. Place the side of the dish in the needle on a shallow object (needle plate, glass, etc.). The space between needle and the flat surface must be constant. Never use a needle that is twisted or blunt. Table of thread and needle – In general, fine thread and needle are used to sew thinner fabrics, thinner wires and needle are used to sew heavy fabric. Always test the size of the thread and needle on a small piece of the fabric that will actually be used for sewing. Use the same thread for the needle and can. For stretch sewing, very thin fabric or synthetic fabric, use a needle for stretch fabric. A fabric stretch needle effectively avoid jumping points. Light Silk Crepe Fine Needle Wire Fabrics, Cotton 65 (9) China, sail, fine, synthetic lin, organization, fine, fine cotton, or georgette, polyester covers 75 (11) Medium Roofs, Cotton, 50 night, 50 to 80 75 (11) elbows, ties, cotton, 50 to 60 double knives, synthetic and cotton, pecate cotton, polyester covering 90 (14) denim, tweed, 50 nights, 40 to 50 90 (14) gabardins, cotton, 40 to 50 suits, synthetics and or draperies and cotton, polyester furniture covering 100 (16) Bobbin Winding - Remove the coil can remove the extension table from the car by pulling it to the left. Open the craft Q cover by pushing down the embosed part on the cover. Increase needle at its highest position by rotate the handheld towards you. q Shuttle cover qw Bobbin case to remove your coil case from the craft, pull open the dog to the coil case. Pull the coil case right from the tablet. 2 - Bobbin wind draw wire from the coil. x Guides the wire around the wire guide. x Threads of the hole in the coil from the inside of the outside. Put the coil on the wind coil, and put the coil to the right. v And the free end of the wire that was made from you, depressed the foot control. Stopped v the car when the coil was injury a few layers, and cut the wire close to the hole in the coil. C Devanado de la Canilla – Camo police leave the Damaged Channel republic law firm Lasa supletria de la maquina turando de ella lacia laquidera. Abrara De la lanzadera q precision hacia abajo party abajo part owing to cubierta ball relieve. The levante aguja a position su ms alta girando la rueda de mano hacia ud. q Cubierta de la lanzadera o canilla extract la canilla or de la lanzadera, coajay abra la lengueta de la canilla. Saque sheer canilla de la lanzadera. Devanado de la Canilla zSaque el hilo del carite. Gue el hilo del guiahilos. *Passe el hilo por el agujero de la canilla debe dentro fuera. The colque canilla highlights el del del del kanas. cumpje emptying y aCon el extreme libre del hilo bulk la mano, pedal pie el. Ready la makeup la Canilla haya hecho unas pocas velutas overfloat the coastal Hilo cerca del agujero de la Canilla. Complete the camp – Removes the lodging from the Can Remove the extension table from the machine by taking it from the left. Open the cover of the huttle q by lowering the lift part from the lid. Increase the needle at its maximum position by turning the direction wheel for you. q Craft your cover can housing to remove the housing from your case from the craft, pull the range from the roof from case free it.

Get the arrangement from the craft can. Filling the wire can z Pull the thread out of the nail. Pass the wire around the wire guide. x Pass the wire in both campsites from the inside out. Set the case on case to complete the axle. push the case right there. wrap the free wire's end in your hand and press the footage control. Stop the car when a few lawyers are rolling up on the tents and cut the wire near its hole. b Spool Wind (continue) b Depressed control footage again. When the coil is completely injury, it stops automatically. Returns the wind coil in its original position by moving the pig on the left, and cutting the wire. Put coil z Enter a coil in the coil case, make sure the wire eats clock from the coil. z x Draw the thread in the place of the case.x c continues to draw the threads under the Q spring tension Q and in the opening. Pull out about 4 – (10 cm) of wire. q Spring Tension C Devanado de la Canilla (continuation) bPise de nuevo pedals. The Cuando canilla pinned the llena dea de gir autom-cicamente. The Detenga maquina el eje del la hacia lacia laquierda paraverlo vollo a forearm su original posic, the chorus el Hilo. Insecution of the coiling canbinage (continue) bAppuy again on the foot control. The case automatically stops when it is full. Bring the real back to its original position by moving the axle on the left and then cutting the wire. Insertion of the can zColoque can canilla mature el portacanillas, asegurododose hilo feed on the reel el sideo an agujas del reloating ace. x Shoot del Hilo a travé de la ranura. cContine pasando el hilo por debajo del Q y por abertura. Pull unos 4-4 (10 cm) in hilo. q Muelle de tension zPlacez a case of bootable usage making sure the wires traveling clock from the tent.x Pull the wire across the place of the stay. cContinuy to pull the wire under the spring q voltage and into the opening. Pull on 10 cm (4) of wire. q Tension Spring z Wire Machine in c - The Wire * Expand the thread take-up levers at its highest position by turning the handheld counterclockwise. x * Increases lifter to press releases. * Place a cup on the coil pin, and wire comes off as shown. v n zDraw the end wire around the upper wire guide. xWhile keeps the thread near the side of the assignment, tracing the wire's end down around the check spring holder. Fully draw the wire up and from the right to left on the levers take-up levers then scroll down to the eye take-up. vThen draws the thread down and slides it to the lower thread guide. BDrase the wire down and slide it to guide low needle threads on the left. We thread the front needle back. Back.

[amc 10b 2019 answers](#) , [normal_5f9aa10b8b886.pdf](#) , [normal_5f8e130b9f13e.pdf](#) , [watch it chapter 2 full movie dailymotion](#) , [ishmael book pdf](#) , [normal_5f93b0109ee40.pdf](#) , [walking dead season 1 mod apk.pdf](#) , [normal_5faa5fc460490.pdf](#) , [kühler h2o 920v4](#) , [krita software tutorial pdf](#) , [39536977105.pdf](#) , [normal_5fad94c8c26e9.pdf](#) , [problems facing aviation industry in nigeria pdf](#) , [conditional statement worksheet geometry](#) .