




I'm not robot



Continue

Dymo labelwriter duo manual

User Guide DYMO® LabelWriter® Label Printers Use print server 154 Dect the printer, and then click Add. The shared printer is added to the Printer List dialog box. The Note LabelWriter Duo printer is actually two Label and Tape printers, so you need to add both printers separately. 5 Close dialody of the printer list. Using a print server • Make sure your print server supports the type of operating system installed on your computer (Windows or Mac OS). • DYMO label printers with earlier versions of firmware do not support print servers. See Printer Firmware Versions that support printing Servers. In general, during the installation of the print server, if you are prompted for a printer or print program, select the option to install the printer driver from the disc and insert the DYMO label SOFTWARE CD into the computer's CD-ROM drive. If the installer does not automatically locate printer drivers, it will run into printer drivers on the CD. If you are prompted to select a printer, select the printer that is physically connected to the print server. To connect a label printer to a printer 1 Connect one end of the USB cable to the USB connector on the label printer, and then connect the other end to the USB connector on the print server. 2 Connect the print server to your network. 3 Connect power to the printer and printer. 4 Ustall and configure the print server on your network. 5 Confirm that you can print to a label printer from the computer you use to install and configure the print server. 6 Add is a printer connected to a print server to other computers in the work force. 1 2 Table of Contents 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16